Monitoring Cruise at the Central Long Island Sound Disposal Site September 1995

Disposal Area Monitoring System DAMOS



Contribution 118 November 1997



US Army Corps of Engineers. New England District

was formed as part of an Environmental Protection Ager various dredged material disposal alternatives. Since 19 1995 REMOTS [®] results from FVP continue to show a la of the mound. However, the effects of a decrease in ava deposit of uncapped UDM. The FVP mound has been m the WES/EPA experimentation has concluded, capping of 14. SUBJECT TERMS Central Long Island Sou Capping Dredged Material (CDM)	91, FVP has displayed instability in tack of a stable, healthy benthic enviro illable oxygen on the organisms inhal ionitored periodically as a source of o f the FVP mound in order to isolate nd (CLIS), Confined Aquatic D	nment with the pro- iting FVP might b comparison for oth the UDM from the isposal (CAD),	esence of depress e amplified due er mounds at CI marine environ 15. NUMBE 16. PRICE C	sed RPD an to the prees JS since its ment is reco R OF PAC	urface sediments. September d OSI values near the center sisting stress of occupying a formation in 1983. Now the ommended. GE 137	
was formed as part of an Environmental Protection Ager various dredged material disposal alternatives. Since 19 1995 REMOTS ^Ф results from FVP continue to show a la of the mound. However, the effects of a decrease in ava deposit of uncapped UDM. The FVP mound has been m the WES/EPA experimentation has concluded, capping or 14. SUBJECT TERMS Central Long Island Sou Capping Dredged Material (CDM)	91, FVP has displayed instability in tack of a stable, healthy benthic enviro- ilable oxygen on the organisms inhat nonitored periodically as a source of o of the FVP mound in order to isolate nd (CLIS), Confined Aquatic D	nment with the proving FVP might be comparison for othe UDM from the UDM from the second (CAD),	esence of depress e amplified due er mounds at CI marine environ	sed RPD an to the preez JS since its ment is reco R OF PA	urface sediments. September d OSI values near the center tisting stress of occupying a formation in 1983. Now the ommended. GE 137	
was formed as part of an Environmental Protection Ager various dredged material disposal alternatives. Since 19 1995 REMOTS ^{Φ} results from FVP continue to show a la of the mound. However, the effects of a decrease in ava deposit of uncapped UDM. The FVP mound has been m the WES/EPA experimentation has concluded, capping of	91, FVP has displayed instability in t ck of a stable, healthy benthic enviro illable oxygen on the organisms inhat nonitored periodically as a source of o f the FVP mound in order to isolate	nment with the pro- pring FVP might b comparison for othe the UDM from the	esence of depress e amplified due er mounds at CI marine environ	sed RPD an to the prees JS since its ment is reco	urface sediments. September d OSI values near the center disting stress of occupying a formation in 1983. Now the pommended.	
 13. ABSTRACT Science Applications International Corporation to 1 September 1995 as part of the Disposal Area Monit 93), CLIS 1994 (CLIS 94), and Field Verification Progr (REMOTS[®]) sediment-profile photography, and geotech rates, and benchic recolonization of the NHAV 93, CLIS The NHAV 93 mound was developed during conducted a total of seven bathymetric, four REMOTS[®] comprehensive time-series data set documents the forma The results of the September 1995 field effort 0.5 m consolidation near the center of the mound. The I sediment horizon throughout the project difficult. Howe UDM, and CDM sediment strata. REMOTS[®] sediment anticipated. A seasonal reduction in dissolved oxygen w (RPD) depths over the NHAV 93 mound as well as the 0 the center and extreme southern and eastern stations desj In September 1994, a disposal buoy marked " Approximately 129,900 m³ of UDM was deposited at the UDM deposit was capped to a thickness of 0.5 to 1.0 m 04 mound approximately 630 m northeast of NHAV 93 the Bathymetric data collected over the CLIS 94 pottom feature is approximately 470 m wide at the center nound, a capped mound developed during the 1989/90 d REMOTS[®] stations in spite of the recent impact of dispo- The FVP mound is a small mound in the nort 	on (SAIC) conducted a monitoring sur- oring System (DAMOS) Program. T am (FVP) mounds and consisted of p- nical coring. These surveying techni & 94, and FVP mounds. the 1993/94 disposal season as part o sediment-profiling, and five geotechni tion of the mound within the containue indicate a moderate amount of conse- heterogeneity of the material collecter wer, indicators such as shell fragmen profile-photography found the biota of ithin the central Long Island Sound r CLIS reference areas. As a result, lo pite the presence of Stage III organisis CDA" was deployed at 41°09.343' M e buoy from late November through I from January through May 1995 with oegan the formation of a second conta- mound exhibited a moderate sized, st r with a mound height of 3.25 m at the isposal season. Benthic recovery of sal and added stress of seasonal hypo- heast corner of CLIS composed of un toy (EPA) and US Army Corps of En-	vey at the Central he field operations recision bathymetr ques were employed f a large scale con- nical coring survey nent cell as well as olidation (0.25 m) d in the five-memb ts, gravel, and det occupying the surfa- egion appeared to wer than expected ns at eleven of this I, 72°53.099' W b nid-December 199 n an estimated volu- tinment ring capab able, and complete te apex. The CLI: CLIS 94 was adva xia. capped UDM drect gineers, Waterway be benthic infauna	Long Island Sou were concentra- ic surveys, Rem ed to monitor the fined aquatic dis sover the NHA's sover the NHA's sover the majority er geotechnical ritus were useful ace sediments of be responsible for organism-sedim the stations over y SAIC to the no 4 to form the for une of 161,000 r le of accommode by capped featur S 94 mound has need with Stage lged from Black vs Experiment Sta	and Disposa ted over the ote Ecologi stability, c posal (CAD V 93 mount solidation and y of NHAV coring data in different the NHAV for shallow r ent index (C er the NHA or shallow r ent index (C er the NHA or shallow r ent index (C er the NHA for the Shallow r ent index (C er the CL completely III organism Rock Harbo tation (WES bitting the s	I Site (CLIS) from 27 Augus New Haven 1993 (NHAV cal Monitoring of the Seaflo ap thicknesses, consolidation) project. SAIC has I since September 1993. The ad benthic recolonization. 93 with several pockets of set makes tracking a single tiating ambient, historic, 93 mound to be recovering edox potential discontinuity SSI) values were found near V 93 mound. he NHAV 93 mound. the CLIS 94 mound. The . The placement of the CLI re CAD mound project. IS seafloor. The new CLIS incorporated the CS-90-1 ns present at the majority of or in the spring of 1983. It S) joint effort to evaluate	
Available from DAMOS Program Ma USACE-NED, 424 Trapelo Road, V 12a. DISTRIBUTION/AVAILABILITY STATE Approved for public release; distribut	Anager, Regulatory Division Valtham, MA 02254-9149 MENT tion unlimited		1	2b. DIST	RIBUTION CODE	
11. SUPPLEMENTARY NOTES	Demision					
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) US Army Corps of Engineers-New England Division 424 Trapelo Road			1	0. SPONS AGENCY DAMOS	SORING/MONITORING REPORT NUMBER S Contribution #118	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Science Applications International Corporation 221 Third Street Newport, RI 02840			8	. PERFO REPORT SA	RMIGORGANIZATIO NUMBER IC No. 373	
SEPTEMBER 1995 6. AUTHOR(S) JOPHN T. MORRIS						
4. TITLE AND SUBTITLE MONITORING CRUISE AT THE CENTRAL	L	SAL SITE,	5	5. FUNDI	NG NUMBERS	
1. AGENCY USE ONLY (LEAVE BLANK)	2. REPORT DATE November 1997	3. F	EPORT TYP	E AND D AL REPO	ATES COVERED RT	
Public reporting concern for the collection of infom searching existing data sources, gathering and mean regarding this burden estimate or any other aspect of Headquarters Services, Directorate for information and to the Office of Management and Support, Pa	mation is estimated to average 1 h suring the data needed and correct of this collection of information in Observations and Records, 1215 perwork Reduction Project (0704	our per response ing and reviewin cluding suggesti Jefferson Davis I -0188), Washing	including the t g the collection ons for reducin Highway, Suite ton, D.C. 2050	ime for re of inform g this burc 21204, Ar 3.	viewing instructions, hation. Send comments len to Washington lington VA 22202-4302	
	REPORT DOCUMENTATION PAGE			form approved OMB No. 0704-0188		

-

-

MONITORING CRUISE AT THE CENTRAL LONG ISLAND SOUND DISPOSAL SITE SEPTEMBER 1995

CONTRIBUTION #118

November 1997

Report No. SAIC 373

Submitted to:

Regulatory Branch New England District U.S. Army Corps of Engineers 424 Trapelo Road Waltham, MA 02254-9149

> Prepared by: John T. Morris

Submitted by: Science Applications International Corporation Admiral's Gate 221 Third Street Newport, RI 02840 (401) 847-4210



US Army Corps of Engineers. New England District

TABLE OF CONTENTS

Ρ	a	g	e
		_	-

LIST EXEC	OF FI	GURES
1.0	INTR	ODUCTION
2.0	MET	HODS10
	2.1	Survey Areas10
	2.2	Bathymetry and Navigation10
	2.3	REMOTS [®] Sediment-Profile Photography14
	2.4	Geotechnical Coring14
3.0	RESI	II TS
5.0	3.1	NHAV 93 Mound
	2.1	3.1.1 Bathymetry 18
		3.1.2 REMOTS [®] Sediment-Profile Photography
		3.1.3 Geotechnical Coring
	3.2	CLIS 94 Mound
		3.2.1 Bathymetry
		3.2.2 REMOTS[®] Sediment-Profile Photography
	3.3	FVP Mound
		3.3.1 Sediment Grain Size and Stratigraphy
		3.3.2 Benthic Community Assessment
	3.4	CLIS Reference Areas
		3.4.1 Sediment Grain Size and Stratigraphy
		3.4.2 Benthic Community Assessment
4.0	DISC	USSION
5.0	CON	CLUSIONS
6.0	REFE	ERENCES
INDE	X	

APPENDICES

LIST OF FIGURES

Page

Figure 1-1.	Location of the Central Long Island Sound Disposal Site and shore station benchmarks
Figure 1-2.	The historic DAMOS and Final Programmatic Environmental Impact Statement boundaries of the Central Long Island Sound Disposal Site over the July 1994 bathymetric survey
Figure 1-3.	September 1993 baseline bathymetry depicting a ring of seven historic disposal mounds with plotted position of the NHAV 93 buoy, 0.25 m contour interval
Figure 1-4.	Depth difference contour chart based on the comparisons of the March 1994 postcap survey versus the September 1993 baseline survey
Figure 2-1.	Base map displaying the bathymetric survey areas and REMOTS [®] stations relative to the Central Long Island Sound Disposal Site boundaries
Figure 2-2.	Comparisons of the two types of tidal data collected for the September 1995 bathymetric surveys
Figure 2-3.	Chart of the 1600 m \times 1600 m survey area with plotted geotechnical core positions and names
Figure 2-4.	Diagram of the URI/MGL large-diameter gravity corer
Figure 3-1.	Bathymetric chart of the 1600 m × 1600 m survey area over the NHAV 93 mound, 0.5 m contour interval
Figure 3-2.	Bathymetric chart of the 1600 m \times 1600 m survey area over the NHAV 93 mound, with mound names, 0.25 m contour interval20
Figure 3-3.	Depth difference plot of the postcap survey of March 1994 versus the September 1995 survey over the NHAV 93 mound, 0.25 m contour interval

LIST OF FIGURES (continued)

Figure 3-4.	Depth difference plot of the baseline survey of September 1993 versus the September 1995 survey, 0.25 m contour interval. Chart represents the total apparent accumulation of dredged material since September 1993
Figure 3-5.	Distribution of RPD (cm) and OSI values over the NHAV 93 mound, overlaid on September 1995 bathymetry and detectable margins of the mound
Figure 3-6.	Distribution of successional stage assemblages over the NHAV 93 mound, overlaid on September 1995 bathymetry and detectable margins of the mound
Figure 3-7.	REMOTS [®] photographs showing the improving conditions at Station 400S over the NHAV 93 mound during the September 1995 (A) survey relative to the July 1994 (B) survey
Figure 3-8.	REMOTS [®] photographs showing the improving conditions at Station CTR over the NHAV 93 mound during the September 1995 (A) survey relative to the July 1994 (B) survey
Figure 3-9.	Location of geotechnical cores GC-1 through GC-11 over the apparent total accumulation of dredged material since September 1993 30
Figure 3-10.	Color geotechnical core descriptions oriented to display the results of the SW-NE transect over the NHAV 93 mound
Figure 3-11.	Color geotechnical core descriptions oriented to display the results of the NW-SE transect over the NHAV 93 mound
Figure 3-12.	Bathymetric chart of the 1000 m × 1000 m survey area over the CLIS 94 mound with plotted CDA 94 buoy positions, 0.25 m contour interval
Figure 3-13.	Depth difference plot of SAIC's July 1994 baseline survey versus SAIC's September 1995 postcap survey, 0.25 m contour interval

iv

LIST OF FIGURES (continued)

	Page
Figure 3-14.	Bathymetric chart of the 675 m \times 500 m area of concentrated analysis over the CS 90-1 mound, SAIC's July 1994 baseline survey, 0.25 m contour interval
Figure 3-15.	Bathymetric chart of the 675 m × 500 m area of concentrated analysis over the CLIS 94 mound UDM deposit, OSI's December 1994 precap survey, 0.25 m contour interval
Figure 3-16.	Depth difference plot of SAIC's July 1994 baseline survey versus OSI's December 1994 precap survey with plotted CDA 94 buoy positions, 0.25 m contour interval
Figure 3-17.	Bathymetric chart of the 675 m \times 500 m area of concentrated analysis over the CLIS 94 mound at interim cap status, OSI's April 1995 interim cap survey, 0.25 m contour interval
Figure 3-18.	Depth difference plot of SAIC's July 1994 baseline survey versus OSI's April 1995 interim cap survey, overlaid with the detectable margin of the UDM deposit, 0.25 m contour interval
Figure 3-19.	Depth difference plot of OSI's December 1994 baseline survey versus OSI's April 1995 interim cap survey, overlaid with the reported 700 yd ³ barge release positions, 0.25 m contour interval
Figure 3-20.	Bathymetric chart of the 675 m \times 500 m area of concentrated analysis over the CLIS 94 mound at postcap status, SAIC's September 1995 postcap survey, 0.25 m contour interval
Figure 3-21.	Depth difference plot of SAIC's September 1995 postcap survey versus OSI's April 1995 interim cap survey with plotted CDA 94 buoy and reported barge release positions, 0.25 m contour interval46
Figure 3-22.	Depth difference plot of SAIC's September 1995 postcap survey versus OSI's December 1994 precap survey, overlaid with the CDA 94 buoy and reported barge release positions, 0.25 m contour interval47

ν

LIST OF FIGURES (continued)

Page

Figure 3-23.	Plot of the three stages of CLIS 94 mound development, overlaid with the CDA 94 buoy positions
Figure 3-24.	Distribution of RPD (cm) and OSI values over the CLIS 94 mound, overlaid on September 1995 bathymetry and final detectable margin of the mound
Figure 3-25.	REMOTS [®] photographs at Station 300S displaying the differences in benthic conditions (deep RPD [A] versus low DO [B]) within the confines of the same station
Figure 3-26.	Distribution of successional stage assemblages over the CLIS 94 mound, overlaid on September 1995 bathymetry and final detectable margin of the mound
Figure 3-27.	Distribution of RPD (cm) and OSI values over the FVP mound55
Figure 3-28.	Distribution of successional stage assemblages over the FVP mound
Figure 3-29.	REMOTS [®] photographs of Stations 100N (A) and 300W (B) displaying differences in benthic conditions between the center and apron of the FVP mound
Figure 4-1.	Position of the Connecticut Department of Environmental Protection Dissolved Oxygen Sampling Stations and bottom DO trends at summer monitoring stations 23, 26, and 27 for 1994 and 199561
Figure 4-2.	Observed changes in bottom DO concentrations at Connecticut Department of Environmental Protection Dissolved Oxygen Sampling Stations H2 and H4 for 1995
Figure 4-3.	Histogram displaying recorded RPD calculations from June 1991, November 1993, and September 1995 at Stations 100E, 100N, 100W, and CTR over the FVP mound

Page

Figure 4-4.	Histogram displaying recorded OSI values from June 1991,
	November 1993, and September 1995 at Stations 100E, 100N, 100W,
	and CTR over the FVP mound

Science Applications International Corporation (SAIC) conducted a monitoring survey at the Central Long Island Sound Disposal Site (CLIS) from 27 August to 1 September 1995 as part of the Disposal Area Monitoring System (DAMOS) Program. The field operations were concentrated over the New Haven 1993 (NHAV 93), CLIS 1994 (CLIS 94), and Field Verification Program (FVP) mounds and consisted of precision bathymetric surveys, Remote Ecological Monitoring of the Seafloor (REMOTS[®]) sediment-profile photography, and geotechnical coring. These surveying techniques were employed to monitor the stability, cap thicknesses, consolidation rates, and benthic recolonization of the NHAV 93, CLIS 94, and FVP mounds.

The NHAV 93 mound represents the culmination of ten years of thoughtful planning and controlled disposal at CLIS. This mound was developed during the 1993/94 disposal season as part of a large scale confined aquatic disposal (CAD) project. From 1984 through 1992, disposal operations at CLIS led to the construction of a ring of disposal mounds. This ring formed an artificial containment cell that was capable of accepting a large volume of unacceptably contaminated dredged material (UDM), limiting the lateral spread of the deposit and, in turn, facilitating efficient capping operations. The NHAV 93 mound was formed by the placement of approximately 590,000 m³ of UDM within the ring of seven historic disposal mounds. The UDM deposit was then covered to a thickness of 0.5 m to 1.0 m by 569,000 m³ of capping dredged material (CDM).

SAIC has conducted a total of seven bathymetric, four REMOTS[®] sedimentprofiling, and five geotechnical coring surveys over the NHAV 93 mound since September 1993. The comprehensive time-series data set documents the formation of the mound within the containment cell as well as its gradual consolidation and benthic recolonization. In addition, the wealth of data has provided SAIC and the US Army Corps of Engineers, New England Division (NED), with significant insight into the short- and long-term effects of disposal and oceanographic processes on large dredged material mounds.

The results of the September 1995 field effort indicate a moderate amount of consolidation (0.25 m) over the majority of NHAV 93 with several pockets of 0.5 m consolidation near the center of the mound. The heterogeneity of the material collected in the five-member geotechnical coring data set makes tracking a single sediment horizon throughout the project difficult. However, indicators such as shell fragments, gravel, and detritus were useful in differentiating ambient, historic, UDM, and CDM sediment strata. REMOTS[®] sediment profile-photography found the biota occupying the surface sediments of the NHAV 93 mound to be recovering as anticipated. A seasonal reduction in dissolved oxygen within the central Long Island Sound region appeared to be responsible for

EXECUTIVE SUMMARY (continued)

shallow redox potential discontinuity (RPD) depths over the NHAV 93 mound as well as the CLIS reference areas. As a result, lower than expected organism-sediment index (OSI) values were found near the center and extreme southern and eastern stations despite the presence of Stage III organisms at eleven of thirteen stations over the NHAV 93 mound.

In September 1994, a disposal buoy marked "CDA" was deployed at 41°09.343' N, 72°53.099' W by SAIC to the northeast of the NHAV 93 mound. Approximately 129,900 m³ of UDM was deposited at the buoy from late November through mid-December 1994 to form the foundation of the CLIS 94 mound. At the conclusion of UDM disposal operations, the CDA buoy was struck by a disposal barge and dragged off-station. The buoy was repositioned to 41°09.334' N, 72°53.084' W before the start of CDM deposition over the CLIS 94 mound. The UDM deposit was capped to a thickness of 0.5 to 1.0 m from January through May 1995 with an estimated volume of 161,000 m³ of CDM. The placement of the CLIS 94 mound approximately 630 m northeast of NHAV 93 began the formation of a second containment ring capable of accommodating a future CAD mound project.

Bathymetric data collected over the CLIS 94 mound exhibited a moderate sized, stable, and completely capped feature of the CLIS seafloor. The new CLIS bottom feature is approximately 470 m wide at the center with a mound height of 3.25 m at the apex. The CLIS 94 mound has completely incorporated the CS-90-1 mound, a capped mound developed during the 1989/90 disposal season. Benthic recovery of CLIS 94 was advanced with Stage III organisms present at the majority of REMOTS[®] stations in spite of the recent impact of disposal and added stress of seasonal hypoxia.

The FVP mound is a small mound in the northeast corner of CLIS composed of uncapped UDM dredged from Black Rock Harbor in the spring of 1983. It was formed as part of an Environmental Protection Agency (EPA) and US Army Corps of Engineers, Waterways Experiment Station (WES) joint effort to evaluate various dredged material disposal alternatives. Since 1991, FVP has displayed instability in the benthic infaunal population inhabiting the surface sediments. September 1995 REMOTS[®] results from FVP continue to show a lack of a stable, healthy benthic environment with the presence of depressed RPD and OSI values near the center of the mound. However, the effects of a decrease in available oxygen on the organisms inhabiting FVP might be amplified due to the preexisting stress of occupying a deposit of uncapped UDM. The FVP mound has been monitored periodically as a source of comparison for other mounds at CLIS since its formation in 1983. Now that the WES/EPA experimentation has concluded, capping of the FVP mound in order to isolate the UDM from the marine environment is recommended.

ix

1.0 INTRODUCTION

The managed disposal of dredged material was introduced to the central Long Island Sound region in October 1973 with the development of the New Haven 1974 (NHAV 74) mound in the center of the newly created New Haven Disposal Site. An estimated 1,150,000 m³ of material dredged from the New Haven Harbor was deposited at this site between October 1973 and March 1977. In 1977, the US Army Corps of Engineers, New England Division (NED), instituted the Disposal Area Monitoring System (DAMOS) Program in response to the recognized need for long-term management and monitoring of the New Haven Disposal Site as well as 10 other disposal sites in New England waters (NUSC 1979). Since 1977, advances in dredged material disposal, precision navigation, and environmental monitoring technology have continually improved the tools used in disposal site management.

In 1979, the configuration of the New Haven Disposal Site was modified, expanding the boundaries of the site and changing its name to Central Long Island Sound Disposal Site (CLIS; SAI 1979). The new disposal site boundaries encompassed a 6.86 km² (2 nmi²) area located approximately 10.39 km (5.6 nmi) south of South End Point, East Haven, Connecticut (Figure 1-1). Since its expansion in 1979, the disposal site shown in DAMOS reports has been centered at 41°08.950' N, 72°52.850' W. However, after recognizing a slight discrepancy, NED began using the set of center coordinates for CLIS as defined in the Final Programmatic Environmental Impact Statement (FPEIS; US Army Corps of Engineers 1982). CLIS is now centered at 41°08.900' N, 72°53.100' W longitude in North American Datum of 1927 (NAD 27), 362 m west-southwest of the historic DAMOS center (Figures 1-1 and 1-2). The reasons for the discrepancy between the historic and FPEIS coordinates are unknown; however, this modification corrects the locational inconsistency. Similar changes are being made for the New London Disposal Site (NLDS) and Cornfield Shoals Disposal Site (CSDS) in the eastern Long Island Sound.

Historically, CLIS has been one of the most active disposal sites in the New England region. The disposal site has received sediments dredged from New Haven, Bridgeport, Stamford, and Norwalk Harbors, as well as adjacent coastal areas. The abundance of disposal activity within the boundaries of the disposal site allowed NED to develop and refine a variety of dredged material management strategies. During the 1978/79 disposal season, subaqueous capping was introduced as a new dredged material management approach with the formation of the Stamford-New Haven mounds (STNH-N and STNH-S; SAIC 1995).

Capping is a containment method which uses sediments determined to be suitable for unconfined open water disposal, or capping dredged material (CDM), to overlay and





Figure 1-1. Location of the Central Long Island Sound Disposal Site and shore station benchmarks



w

isolate deposits of unacceptably contaminated dredged material (UDM) from the environment (Fredette 1994). As a result of the operational success of the 1979 capping project, many additional capped mounds have been formed at CLIS (SAIC 1995).

From 1977 through 1983 the site management strategy at CLIS entailed the formation of many independent mounds over the given area of the disposal site. Each mound was monitored individually, assessing mound stability, cap thickness, benthic recolonization status, etc. Although this practice was highly successful, the overall capacity of the disposal site was compromised due to the unusable area between the discrete sediment mounds (Morris et al. 1996).

In 1983, a new management strategy was instituted at CLIS. Utilizing the ten-year dredging cycle that exists in the central Long Island Sound region, NED managed the deposition of small to moderate volumes of dredged material at CLIS to form a disposal mound ring. Upon completion in 1992, this network of disposal mounds formed an artificial containment cell that was capable of accepting a large volume of UDM, limiting the lateral spread of the deposit, and facilitating efficient capping operations.

The containment ring was employed during the 1993/94 disposal season as part of the New Haven Harbor Capping Project. In September 1993, the NHAV buoy was placed in the center of seven historic disposal mounds ($41^{\circ}09.122'$ N, $72^{\circ}53.453'$ W) designating the disposal point for approximately 590,226 m³ of UDM dredged from the inner New Haven Harbor (Figure 1-3). The UDM deposit was then capped to a thickness of 0.5 m to 1.0 m with an estimated barge volume of 569,287 m³ of outer New Haven Harbor CDM, forming the New Haven 1993 (NHAV 93) mound. Upon completion of disposal and capping operations in March 1994, the NHAV 93 mound displayed a height of 2.5 m and an overall diameter of 800 m (Figure 1-4; Morris et al. 1996).

Due to the utilization of an artificial containment structure, the NHAV 93 mound is considered a confined aquatic disposal (CAD) mound. The use of the disposal mound ring significantly reduced the outward migration of the UDM mound apron relative to an uncontained UDM deposit. As a result, cap material distribution was concentrated over a smaller area, decreasing the total volume of CDM required to cap the inner New Haven Harbor sediments (Morris et al. 1996). The completed CAD mound was found to be broad, stable, adequately capped, and exhibiting a CDM to UDM ratio of 0.96:1.0 (Morris and Tufts 1997). In the past, CDM to UDM ratios varied from 2:1 to 6:1 when initiating a capping operation on a flat or gently sloping area of seafloor. The NHAV 93 mound represents the first capped mound composed of a smaller volume of CDM than the initial UDM deposit.



September 1993 Baseline Bathymetry

Figure 1-3. September 1993 baseline bathymetry depicting a ring of seven historic disposal mounds with plotted position of the NHAV 93 buoy, 0.25 m contour interval





Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

Y

In September 1994, the CDA buoy was deployed over the historic CS-90-1 mound at 41°09.343' N, 72°53.099' W, approximately 630 m northeast of the NHAV 93 mound apex. The placement of a moderate-sized, capped mound in close proximity to the NHAV 93 mound complex began the formation of a second containment ring capable of accommodating a future CAD mound project. In addition, the deposition of new material over CS-90-1 was intended to cover the smaller CS-90-1 capped mound, further isolating its UDM deposit and conserving the usable surface area of the CLIS seafloor.

An estimated barge volume of 129,900 m³ of UDM was released at the CDA buoy from late November through mid-December 1994. Toward the end of UDM disposal activity, the CDA buoy was struck by a disposal barge and dragged off-station. The buoy was repositioned at 41°09.334' N, 72°53.084' W on 27 December 1994 before the start of CDM deposition. During capping operations, the UDM deposit was covered to a thickness of 0.5 to 1.0 m from January through May 1995 with an estimated volume of 161,000 m³ of CDM.

In 1983, the Field Verification Program (FVP) mound was formed in the northeastern corner of CLIS as the subaqueous disposal component of a joint research effort between the US Environmental Protection Agency (EPA) and US Army Corps of Engineers, Waterways Experiment Station (WES). The two agencies were evaluating upland containment, wetland creation, and subaqueous disposal alternatives for UDM (Peddicord 1988). The FVP mound is a small mound composed of 55,000 m³ of uncapped UDM dredged from Black Rock Harbor in the spring of 1983 (Morton 1983). Since 1991, FVP has displayed instability in the benthic infaunal population inhabiting the surface sediments, suggesting an increase in environmental stress.

Science Applications International Corporation (SAIC) conducted a monitoring survey at CLIS from 27 August to 1 September 1995 as part of the DAMOS Program. The field efforts were concentrated over the NHAV 93, CLIS 94, and FVP disposal mounds, and consisted of bathymetric profiling, Remote Ecological Monitoring of the Seafloor (REMOTS[®]), and geotechnical coring. Precision bathymetry and REMOTS[®] technology are well-tested and highly regarded methods of investigating the properties and processes of dredged material disposal within the DAMOS tiered monitoring protocols. The use of geotechnical coring is not a routine monitoring approach but is used in the special study of dredged material mounds to improve our understanding of the dynamics and mass properties of these mounds.

The DAMOS tiered monitoring protocols are based on the use of a control or alternate condition to provide solid statistical testing and serve as a foundation for experimental design (Germano et al. 1994). Three reference areas surrounding CLIS are

used as zones of primary control to allow comparisons between the surface sediments of the disposal mounds and ambient bottom. CLIS-REF (41°08.085' N, 72°50.109' W), 2500W (41°09.254' N, 72°55.569' W), and 4500E (41°09.254' N, 72°50.565' W) are devoid of dredged material and physically, chemically, and biologically represent the ambient bottom of CLIS. The DAMOS Program uses a multiple reference approach to strengthen the statistical models as well as provide contingencies for acute benthic disturbances (i.e., trawling) that affect smaller areas of seafloor at a reference site before or during field operations causing degradation of the data collected.

The objectives of the September 1995 field operations were to

- conduct two bathymetric surveys over CLIS to examine any topographical changes in the NHAV 93 mound and delineate the dredged material footprint of the new CLIS 94 capped mound;
- assess the benthic recolonization status of the NHAV 93, CLIS 94, and FVP mounds relative to the three surrounding CLIS reference areas; and
- sample the various layers of sediment that make up the NHAV 93 mound and quantify the amount of dredged material consolidation and de-watering within those layers.

The September 1995 field effort tested the following predictions:

- Small to moderate amounts of consolidation will be found over the majority of the NHAV 93 mound, while the CLIS 94 mound will be of moderate size, conical in shape, and fully capped.
- The sediments of NHAV 93 are expected to be supporting Stage II and Stage III individuals over the surface of the mound in accordance with the DAMOS tiered monitoring protocols.
- The benthic community over the CLIS 94 mound should consist primarily of Stage I individuals with some progression into Stage II assemblages as predicted by the DAMOS tiered monitoring protocols.
- The conditions over the FVP mound should have returned to a state similar to the three CLIS reference areas; however, seasonal changes in water quality parameters may increase the susceptibility of the benthic community to environmental stress relative to the reference areas.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

• Consolidation of the NHAV 93 mound is expected to obscure the UDM/CDM interface within the geotechnical cores.

2.0 METHODS

2.1 Survey Areas

In order to fulfill the objectives of the 1995 CLIS monitoring survey, two bathymetric survey areas were defined over the CLIS 94 and NHAV 93 disposal mounds. The survey over the CLIS 94 mound was 1000 m \times 1000 m, centered on the first position of the 1994 CDA buoy (41°09.343' N, 72°53.099' W). A total of 41 survey lanes at 25 m lane spacing were required to delineate the topography of the new CLIS 94 mound (Figure 2-1). The second, larger survey was conducted over a 1600 m \times 1600 m area, and centered at 41°09.125' N, 72°53.413' W (Figure 2-1). The layout of this survey was identical to the surveys run over the NHAV 93 mound in the 1993 and 1994 disposal seasons, requiring 65 survey lanes to map the changes in the now historic NHAV 93 mound. Detailed bathymetric charts were generated for both areas to quantify mound height, lateral distribution of dredged material, and position relative to other disposal mounds.

Ξ.

2.2 Bathymetry and Navigation

The SAIC Integrated Navigation and Data Acquisition System (INDAS) provided the precision navigation and data collection required for all SAIC field operations. This system utilizes a Hewlett-Packard 9920[®] series computer to provide real-time navigation, as well as collect position, depth, and time data for later analysis. A Del Norte Trisponder[®] System provided positioning to an accuracy of ± 3 m. Shore stations were established along the Connecticut coast at the known benchmarks of Stratford Point (41°09.112' N, 72°06.227' W) and Lighthouse Point (41°14.931' N, 72°54.255' W) (Figure 1-1). A detailed description of the navigation system and its operation can be found in the DAMOS Navigation and Bathymetry Reference Report (Murray and Selvitelli 1996).

An ODOM DF3200 Echotrac[®] Survey Fathometer with a narrow beam, 208 kHz transducer measured individual depths to a resolution of 3.0 cm (0.1 ft) as described in DAMOS Contribution No. 48 (SAIC 1985). Depth values transmitted to INDAS were adjusted for transducer depth. The acoustic returns of the fathometer can reliably detect changes in depth of 20 cm or greater due to the accumulation of errors introduced by the positioning system, tidal corrections, changes in sound velocity through the water column, the slope of the bottom, and vertical motion of the survey vessel.

The expanding resources of the Internet have allowed SAIC to access the National Oceanographic and Atmospheric Administration (NOAA), Ocean and Lake Levels



Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

Division's (OLLD) National Water Level Observation Network. This network is composed of 181 water level stations that are located throughout the Great Lakes and coastal regions of United States interest. These stations are equipped with the Next Generation Water Level Measurement System tide gauges and satellite transmitters that have collected and transmitted tide data to the central NOAA facility every six minutes, since 1 January 1994.

Observed tide data are available 1 to 6 hours from the time of collection in a station datum or referenced to Mean Lower Low Water (MLLW) and based on Coordinated Universal Time (UTC). For the 1995 CLIS surveys, data from NOAA tide station 8467150 in Bridgeport Harbor, Bridgeport, CT, were used for tidal calculations. The NOAA 6-minute tide data were downloaded in the MLLW datum and corrected to local time, and tidal differences based on the entrance to New Haven Harbor, New Haven, CT, were applied. ×

In order to make valid comparisons between present and past bathymetric surveys of the area, the July 1994 and March 1994 bathymetry models were corrected to observed MLLW. The CLIS 1993 baseline survey of the project area was previously corrected to MLLW using the predicted tides for those survey days; therefore, no re-calculation was required.

During the bathymetric survey, a Seabird Instruments, Inc. SBE 26-03 Sea Gauge wave and tide recorder was used to collect tidal data on-site. The tide gauge, deployed in the survey area, recorded pressure values every six minutes. After conversion, the pressure readings provided a constant record of tidal variations in the survey area based on a mean tidal level (MTL) datum. These observed tidal data were later used to compare and verify the corrected NOAA data generated from the Bridgeport Harbor station (Figure 2-2).

A Seabird Instruments, Inc. SEACAT SBE 19-01 Conductivity, Temperature, and Depth (CTD) probe was used to obtain sound velocity measurements at the start, midpoint, and end of each survey day. The data collected by the CTD probe were bin-averaged to 1 meter depth intervals to account for any pycnoclines, rapid changes in density that create distinct layers within the water column. A mean sound velocity was then calculated using the bin-averaged values.

The bathymetric data were analyzed using SAIC's Hydrographic Data Analysis System (HDAS), version 1.03. Raw bathymetric data were imported into HDAS, corrected for sound velocity, and standardized to MLLW using the NOAA observed tides. The bathymetric data were then used to construct depth models of the surveyed area. A



Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

13

X.

detailed discussion of the bathymetric analysis technique is provided in the DAMOS Navigation and Bathymetry Reference Report (Murray and Selvitelli 1996).

2.3 **REMOTS®** Sediment-Profile Photography

REMOTS[®] photography was used to detect the distribution of dredged material layers, map benthic disturbance gradients, and monitor the benthic infaunal recolonization and/or successional status of the NHAV 93, CLIS 94, and FVP mounds relative to the CLIS reference areas. Cross-sectional photographs of the top 20 cm of sediment were taken for analysis and intercomparison with the adjacent CLIS reference areas.

Three replicate photographs were taken at thirteen stations over each of the three disposal mounds (Figure 2-1). The REMOTS[®] sampling grids over the disposal mounds formed a cross-shaped pattern with three stations along each of four arms and one station in the center. The REMOTS[®] survey over the NHAV 93 mound was centered at 41°09.122' N, 72°53.453' W with station spacing at 200 m. The CLIS 94 and FVP grids, centered at 41°09.343' N, 72°53.099' W and 41°09.390' N, 72°51.750' W, respectively, were based on the same cross-shaped pattern, but sampled every 100 m (Figure 2-1; Appendix A: Table 2-1).

Data from three reference areas (CLISREF, 2500W, and 4500E) were used for comparison of ambient central Long Island Sound sediments relative to the sediments deposited at CLIS through disposal operations. Reference areas 2500W (41°09.254' N, 72°55.569' W) and 4500E (41°09.254' N, 72 50.565' W) were sampled at four randomly selected stations. CLISREF (41°08.085' N, 72°50.109' W) was sampled at five randomly selected stations (Figure 2-1; Appendix A: Table 2-1).

2.4 Geotechnical Coring

The geotechnical coring operations completed on 28 and 29 August were the final replicates collected for the NHAV 93 project. A total of eleven sediment cores were collected from seven stations oriented to produce a cross-section of the NHAV 93 mound. The cores were obtained in an SAIC and University of Rhode Island (URI) joint effort. The sampling scheme was centered on the NHAV 93 buoy position (41°09.122' N, 72°53.453' W). Cores GC-1 through GC-5 and GC-8 through GC-11 were taken in a northeast-southwest transect across the NHAV 93 mound. Cores GC-6 and GC-7 were obtained on a northwest-southeast transect of NHAV 93 mound (Figure 2-3; Appendix A: Table 2-2).



Figure 2-3. Chart of the 1600 m \times 1600 m survey area with plotted geotechnical core positions and names

The sediment cores were obtained with the use of the PVC version of the University of Rhode Island/Marine Geomechanics Laboratory (URI/MGL) large-diameter gravity corer (LGC; Figure 2-4; Silva et al. 1996). The core barrel consists of a 3 m (10 ft) section of Schedule 40 PVC piping (10.2 cm or 4.0 I.D.) and includes a nose cone and core catcher on the end.

All cores were transported back to the URI laboratory facilities and refrigerated during storage. The CLIS sediment cores were processed to obtain overall sediment composition, bulk density, water content, grain size, Atterberg Limits, specific gravity, and shear strength (Silva et al. 1996). A detailed description of the methods used for the analysis of sediment cores GC-1 through GC-11 will be included in a report submitted by Armand J. Silva, P.E., of Geotechnical Consulting Engineers.





Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

3.0 RESULTS

3.1 NHAV 93 Mound

3.1.1 Bathymetry

Seven bathymetric and three REMOTS[®] sediment-profiling surveys were conducted over the NHAV 93 mound since September 1993 to monitor the progress of the CAD mound construction and consolidation over time. The latest bathymetric survey (1600 m × 1600 m), eighteen months after capping operations were completed, displays a mound complex approximately 820 m wide and composed of eight disposal mounds (CLIS 87, CLIS 88, CLIS 89, CLIS 90, CLIS 91, SP, NORWALK, and NHAV 93) (Figures 3-1 and 3-2). Overall, little change in size or shape was detected in the mound complex relative to previous surveys, indicating continued lateral stability.

Depth difference calculations detected 0.25 m of consolidation over the majority of the NHAV 93 mound in comparison to the postcap bathymetric survey of March 1994 (Figure 3-3). Smaller pockets of 0.50 m of consolidation were detected near the center of the NHAV 93 mound. Comparisons with the September 1993 baseline survey calculated the total accumulation of material within the 2.56 km² area over the past two years. The depth difference contour plot displays the central NHAV 93 mound with a height of 2.25 m at the apex and a diameter of approximately 800 m (Figure 3-4). In addition the CLIS 94 mound is clearly visible to the northeast. A ridge of dredged material up to 0.5 m thick connects the two mounds, forming a berm that could be useful in containing a future UDM deposit.

3.1.2 REMOTS[®] Sediment-Profile Photography

The REMOTS[®] sediment-profile photographic survey over the NHAV 93 mound was conducted to evaluate the recolonization status of the CAD mound in comparison to the July 1994 survey, as well as to search for evidence of surface layer consolidation, bedload transport, and oxidation within the surface sediment layers. Complete REMOTS[®] results for the NHAV 93 disposal mound are available in Appendix B Table 1.

3.1.2.1 Sediment Grain Size and Stratigraphy

Grain size and surface roughness data indicated no distinct pattern at the NHAV 93 disposal mound. The major modal grain size at every station was >4 phi, indicating no significant coarsening of surface CDM due to bedload transport of fine-grained material. Boundary roughness values ranged from 0.42 cm to 1.82 cm with the lowest surface



Figure 3-1. Bathymetric chart of the $1600 \text{ m} \times 1600 \text{ m}$ survey area over the NHAV 93 mound, 0.5 m contour interval





Figure 3-2. Bathymetric chart of the $1600 \text{ m} \times 1600 \text{ m}$ survey area over the NHAV 93 mound, with mound names, 0.25 m contour interval

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Figure 3-3. Depth difference plot of the postcap survey of March 1994 versus the September 1995 survey over the NHAV 93 mound, 0.25 m contour interval



Figure 3-4. Depth difference plot of the baseline survey of September 1993 versus the September 1995 survey, 0.25 m contour interval. Chart represents the total apparent accumulation of dredged material since September 1993.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

disturbance values (<0.5 cm) concentrated at the center of the mound (CTR, 200E, 200S: Appendix A: Table 3-1a). The primary cause of boundary roughness was biogenic activity within surface sediments.

The replicate-averaged mean camera penetration ranged from 12.86 cm to 18.91 cm (Appendix A: Table 3-1a). Dredged material was absent at three stations (400N, 600N, 600W), and measured replicate-averaged dredged material thicknesses ranged from 3 cm at 600S to full penetration (20 cm) at many stations (Appendix A: Table 3-1a). The apparent absence of dredged material at stations 400N, 600N, and 600W may be attributed to complete reworking of historical dredged material, to the extent that there are no recognizable indicators. Redox rebound intervals, areas of intermittent or seasonal oxidation below the oxidized surface layer, were noted at several stations, including two of the three stations which had no measurable dredged material (400N, 600N).

3.1.2.2 **Benthic Community Assessment**

Three parameters were used to assess the benthic recolonization rate and overall health of the project mounds relative to the CLIS reference areas. The apparent Redox Potential Discontinuity (RPD) depth, infaunal successional status, and the Organism-Sediment Index (OSI) were mapped on station location plots to outline the biological conditions at each station.

The apparent RPD depth is the depth of oxygenation in the upper sediment layers. This value indicates dissolved oxygen conditions within sediment pore water as well as the availability and consumption of molecular oxygen (O_2) in the surface sediments. Since actual oxygen status in the sediment is not measured, the apparent RPD is estimated by measuring the thickness of the layer of high reflectance in contrast to the usually gray to black reduced sediments at depth (Rhoads and Germano 1982).

Replicate-averaged RPD values over the NHAV 93 mound ranged from 0.91 cm at 600E to 4.23 cm at 400E, indicating improvement relative to the 1994 survey, especially at the stations previously exhibiting slow benthic recovery (Figure 3-5; Appendix A: Tables 3-1a and 3-1b). RPDs of < 2 cm were measured at the central, south, and east sections of the sampling grid (CTR; 200E, W, and S; 400S; and 600S and E). Station 600E, displaying a relatively shallow RPD depth, has probably been affected by the recent deposition of CDM over the CLIS 94 mound reducing the level of oxidation in the surface sediment layers. However, the mean RPD value for the entire project area was 2.14 cm, indicating improving conditions relative to the 0.78 cm RPD value for July 1994. Neither methane nor low dissolved oxygen was noted in any photograph.



Figure 3-5. Distribution of RPD (cm) and OSI values over the NHAV 93 mound, overlaid on September 1995 bathymetry and detectable margins of the mound

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

The mapping of successional stages is based on the theory that organism-sediment interactions follow a predictable sequence after a major seafloor disturbance (Rhoads and Germano 1982). This sequence is defined by end-member assemblages of benthic organisms. Stage I is made up of pioneering assemblages usually consisting of dense aggregations of near-surface, tube-dwelling polychaetes. If left undisturbed, Stage II infaunal deposit feeders such as shallow-dwelling bivalves or tubicolous amphipods then colonize the recovering seafloor. Stage III organisms are generally head-down deposit-feeding invertebrates whose presence results in distinctive subsurface feeding voids. Stage III taxa are associated with relatively low-disturbance regimes (Rhoads and Germano 1986).

Organism-sediment index values are calculated by summarizing the apparent RPD depth, successional status, and indicators of methane or low oxygen. OSIs can range from -10 (azoic with methane gas present in sediment) to 11 (aerobic bottom with deep apparent RPD, evidence of mature macrofaunal assemblage, and no apparent methane). OSI values are useful in mapping disturbances and quantifying ecosystem recovery (Rhoads and Germano 1982).

Eleven stations within the thirteen-station survey grid showed evidence of Stage III organisms (Figure 3-6). The most common stages noted in the replicate photographs were Stage I and Stage I on III. Replicate median OSIs range from 2.5 at 600E (low RPD, no Stage III due to recent CDM deposition) to 11 at 400E (Figure 3-6; Appendix A: Table 3-1a). Low OSIs (<6) are concentrated at the center (CTR, 200E, 200S), and at the extremes of the southern and eastern legs of the grid (600S, 600E). Overall, the mean OSI value for the NHAV 93 mound was 6.4, a substantial improvement over the July 1994 value of 3.5.

The results of the July 1994 REMOTS[®] survey indicated the presence of three areas of concern (CTR, 200N, and 400S; Morris and Tufts 1997). All three stations exhibited shallow to diffusional RPD depths, limited recolonization, and lower OSI values than anticipated. As part of the DAMOS tiered monitoring protocols, sediment from stations CTR, 200N, and 400S was collected and subjected to *Ampelisca* bioassay testing for toxicity. No significant differences in mortality were found between the sediment samples originating from NHAV 93 stations CTR, 200N, and 400S and the sediments collected from CLIS-REF (Mueller 1994). As a result, no action was taken at NHAV 93 (i.e., cap supplementation) and the stations were closely monitored for changes in benthic conditions (Morris and Tufts 1997).

The September 1995 REMOTS[®] results indicate that, in general, the NHAV 93 mound is recovering from the impact of dredged material disposal as predicted (Germano et al. 1994). The three stations that exhibited poor benthic conditions with low RPDs in


Figure 3-6. Distribution of successional stage assemblages over the NHAV 93 mound, overlaid on September 1995 bathymetry and detectable margins of the mound

the 1994 survey (CTR, 200N, 400S) showed improvement, although two replicates at CTR had thin and patchy RPD and low OSI values of 2 and 3 (Figures 3-7 and 3-8). Comparisons of the 1995 NHAV 93 REMOTS[®] results to the reference areas indicate the oxygenation status at the sediment/water interface over the region may have been affected by seasonal hypoxia. As a result, RPD and OSI values on the mound and in the reference areas may have decreased in response to the reduction in available oxygen.

3.1.3 Geotechnical Coring

A total of eleven geotechnical cores were collected to provide a deep, crosssectional view of the multiple sediment layers that make up the NHAV 93 mound (Figure 3-9; Appendix A: Table 2-2). Seven cores with penetration depths varying from 131 cm (GC-9) to 272 cm (GC-6) were split, visually described, and analyzed for the properties listed in Section 2.4 of this document. These seven cores represent the end-member of a five-core data set collected over the NHAV 93 mound at different stages of development (baseline, precap, postcap, four months postcap, and eighteen months postcap; Appendix C: Table 1). Graphics depicting the entire time-series data set are provided in Appendix C. A report pertaining to the geotechnical analysis of cores GC-1 through GC-11 will be included in a final report submitted by Armand J. Silva, P.E., of Geotechnical Consulting Engineers.

Core GC-5 was obtained over the southwest flank of the NHAV 93 mound (41°08.996' N, 72°53.629' W) and penetrated 269 cm into the sediments (Figure 3-9). The visual core description indicates the first 180 cm of material constitutes the New Haven project CDM (Figure 3-10). The CDM layer is composed of several sediment strata of soft, black and olive-gray sands, silts, and clays. A thin layer of New Haven UDM, olive-grey clayey silt, was visible from 180 cm to 200 cm of penetration. A 10 cm to 15 cm layer of dark silt is representative of the historic dredged material that makes up the CLIS 88 and Norwalk mound aprons. The remaining 55 cm of sediment collected in Core GC-5, olive-gray, clayey silt with shell fragments, is typical of ambient, basement material at CLIS.

Core GC-10 was taken approximately 75 m southwest of the NHAV 93 mound center (41°09.075' N, 72°53.521' W; Figure 3-9). A total of 248 cm of CDM, UDM, and historic dredged material was recovered in GC-10. The top 134 cm of sediment was composed of soft, black, clayey silt with organics and shell fragments (Figure 3-10). No distinct horizon was visually detected between New Haven cap and dredged material layers; however, the UDM/CDM interface is estimated at approximately 100 cm of penetration. From 100 cm to 218 cm of penetration this core is made up of the various layers of silt, sand, and gravel. The division between New Haven dredged material and













ie.

historic dredged material exists at 215 cm. No ambient material was sampled in Core GC-10.

Core GC-3B, collected over the center of the NHAV 93 mound (41°09.134' N, 72°53.458' W), penetrated 185 cm into the New Haven sediments (Figure 3-9). The core description indicates that the top 93 cm is composed of two layers of black, clayey silt, representative of the CDM layer (Figures 3-10 and 3-11). The remaining 92 cm of sediment displayed the various strata of the UDM deposit with alternating layers of silt and sands. The multiple sediment horizons within the UDM component depict the heterogeneity of material disposed over the center of the NHAV 93 mound.

Core GC-9, obtained approximately 100 m northeast of the NHAV 93 mound apex (41°09.175' N, 72°53.407' W), penetrated 131 cm into the New Haven Harbor sediments (Figure 3-9). A visual description of Core GC-9 shows three layers of silt, sand, and shell fragments making up the 89 cm thick cap (Figure 3-10). The sediment sampled from 90 cm to 110 cm was a uniform black, clayey silt and considered to be UDM. The second UDM stratum, a layer of brown to black sand and gravel, was visible from 111 cm to the penetration limit.

Core GC-11 was collected on the northeast flank of the NHAV 93 mound (41°09.264' N, 72°53.306' W) and is composed of both NHAV 93 and CLIS 94 dredged material (Figure 3-9). The top 60 cm of sediment in Core GC-11 is consistent with the clayey silt material used as CDM over the CLIS 94 mound (Figure 3-10). The alternating layers of dark olive-gray and black clayey silt that extends from 60 cm to 120 cm correspond to the NHAV 93 cap material, as collected in previous cores. New Haven UDM was sampled at 120 cm of penetration and meets the dark, olive-gray, basement material at 155 cm. The basement material is visible from 155 cm to the penetration limit of 262 cm.

Core GC-7, collected 50 m from the center of the mound, represents the southeast quadrant of NHAV 93 (Figure 3-9). The core penetrated 223 cm into the sediments, providing a cross-section of the CDM and UDM making up the NHAV 93 mound as well as the ambient basement material (Figure 3-11). The top 67 cm of penetration represents the clayey silt cap over the UDM deposit. Layers of soft black, and an olive-gray, clayey silt overlay 147 cm of New Haven dredged material composed of a heterogenous mixture of clay, silt, sand, and gravel. The bottom 9 cm of Core GC-7 is composed of olive-gray silt, the ambient sediment at CLIS.

Core GC-6 was obtained 60 m northwest of the mound center (41°09.182' N, 72°53.509' W) and penetrated 272 cm through NHAV 93 sediments and historic dredged Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Figure 3-11. Color geotechnical core descriptions oriented to display the results of the NW-SE transect over the NHAV 93 mound

material into ambient bottom (Figure 3-9). The top 70 cm of sediment in GC-6 is composed of black, clayey silt with traces of sand and shell and is representative of New Haven CDM (Figure 3-11). The second layer of sediment extends from 70 cm down to 122 cm and is similar to the cap material but displays a noticeable increase in water content. As a result, the second stratum is likely to be a constituent of the New Haven UDM. Two thin layers of sands and gravel also appear to be part of the heterogenous UDM deposit. From 123 cm to 210 cm of penetration, several strata of clays, silts, and sands make up a deposit of historic dredged material originating from disposal activity at the CLIS 89 mound.

3.2 CLIS 94 Mound

3.2.1 Bathymetry

The new CLIS 94 mound is evident in both the large 2.56 km^2 (1600 m × 1600 m) and the smaller 1.0 km² (1000 m × 1000 m) survey areas. The mound is approximately 490 m wide at the center with a minimum depth of 15.75 m (Figure 3-12). The CLIS 94 mound is irregularly shaped with the apex of the mound 20 m northwest of the first position of the 1994 "CDA" disposal buoy (CDA #1). The mound becomes broader and less pronounced as it extends to the south. The new mound has completely incorporated the historic CS 90-1 mound and encroaches on the northeast flank of the historic CLIS 90 mound. Depth difference plots indicate a mound height of 3.0 m at the apex (Figure 3-13).

Barge logs indicated that approximately 290,900 m³ of dredged material was released at the CDA 94 buoy positions. Volume calculations based on depth differences between the July 1994 and September 1995 surveys indicate that 169,600 m³ of sediment accumulated in the vicinity of the disposal buoy (Appendix A: Table 3-2). A large percentage of the 121,300 m³ mass balance shortfall can be accounted for by restricting the size of the analysis models and closely monitoring the development of the CLIS 94 mound. The refocused analysis of the CLIS 94 bathymetric data has revealed a significant amount of consolidation, mainly due to compression and de-watering of the UDM deposit at the center of the mound during capping operations.

Bathymetric survey data collected by Ocean Surveys, Inc. (OSI) of Old Saybrook, Connecticut, at the precap (18 December 1994) and interim cap (23 April 1995) stages of development, in conjunction with SAIC's baseline (July 1994) and postcap (September 1995) surveys, were used to document the development of the CLIS 94 mound as well as detect significant amounts of central mound consolidation. By performing several depth







Figure 3-13. Depth difference plot of SAIC's July 1994 baseline survey versus SAIC's September 1995 postcap survey, 0.25 m contour interval

differencing routines with the four bathymetric data sets, both total accumulations and apparent losses of material can be identified.

By comparing a scaled down version of SAIC's baseline survey in July 1994 to the OSI precap bathymetry, a UDM deposit with a height of 2.75 m and a width of 380 m was detected south of the CDA buoy positions (Figures 3-14, 3-15, and 3-16). The apex of the UDM mound was located approximately 145 m south of the CDA #1 buoy position. DAMOS disposal logs reported the deposition of approximately 129,900 m³ of UDM at CLIS between the dates of 30 November and 13 December 1994 (Appendix D: Table 1). Volume difference calculations detected a total accumulation of 114,700 m³ of new material in the vicinity of the CDA buoy (Appendix A: Table 3-2). By utilizing the bathymetric profile of the disposal mound at the precap stage of development, calculations based on successive bathymetric surveys accounted for 88% of the barge log estimates submitted by on-site inspectors. These findings represent extremely good agreement between the two methods of volume estimates (barge volume vs. sequential bathymetric survey).

The first phase of capping over the CLIS 94 mound was performed from 16 January 1995 through 22 April 1995 (Appendix D: Table 2). During that time period an estimated barge volume of 41,700 m³ of CDM was released over the initial UDM deposit, isolating the majority of the contaminated material from the sediment/water interface. An interim cap bathymetric survey was performed on 23 April 1995 to document the progress of capping operations. The depth difference calculations based on comparisons of the April 1995 interim cap and July 1994 baseline surveys show the total accumulation of material over the CLIS 94 mound (Figures 3-17 and 3-18). A maximum height of 2.75 m was detected over the CLIS 94 mound, and the deposition of CDM has caused the dredged material apron to expand to the north, east, and south, increasing its diameter to approximately 490 m.

Further bathymetric analysis between the December 1994 and April 1995 bathymetric surveys revealed a large pocket of consolidation over the center of the disposal mound. Depth difference plots indicate a net loss in mound height, up to 1.0 m relative to the precap stage of development (Figure 3-19). The deposition of 41,700 m³ of capping material over the UDM deposit caused the formation of three peaks of CDM approximately 1.25 m thick over the north, southeast, and southwest regions of the mound. The majority of the CDM was reportedly released over the fringes of the consolidation pocket during the initial stages of capping operations (Figure 3-19). Volume calculations detected 38,664 m³ of new material over the restricted analysis area, which is considered to make up the ring of accumulation around the CLIS 94 mound. In addition, a negative volume of 26,500 m³



Figure 3-14. Bathymetric chart of the 675 m × 500 m area of concentrated analysis over the CS 90-1 mound, SAIC's July 1994 baseline survey, 0.25 m contour interval



Figure 3-15. Bathymetric chart of the 675 m × 500 m area of concentrated analysis over the CLIS 94 mound UDM deposit, OSI's December 1994 precap survey, 0.25 m contour interval











Figure 3-18. Depth difference plot of SAIC's July 1994 baseline survey versus OSI's April 1995 interim cap survey, overlaid with the detectable margin of the UDM deposit, 0.25 m contour interval



Phase 1 Apparent CDM Thickness Depth Difference

Figure 3-19. Depth difference plot of OSI's December 1994 baseline survey versus OSI's April 1995 interim cap survey, overlaid with the reported 700 yd³ barge release positions, 0.25 m contour interval

of material was found and is considered to be the product of the central mound consolidation (Appendix A: Table 3-2).

These results suggest that the amount of consolidation was significant, concentrated in the UDM deposit, and expedited by the placement of capping material. The area of dredged material subsidence showed an overall reduction in height up to 1.0 m beyond the thickness of the new cap material. This major dredged material consolidation within the center of the mound is responsible for 22% of the 121,300 m³ mass balance shortfall experienced in the standard baseline to postcap volume difference calculations.

From 24 April to 27 May 1995 the final 119,300 m³ of capping was released over the CLIS 94 mound (Appendix D: Table 2). The bottom feature was resurveyed in September 1995, three months after capping operations were completed (Figure 3-20). Comparisons between the September postcap and April interim cap surveys show the additional capping material placed over the CLIS 94 mound (Figure 3-21). Major accumulations of CDM were detected in the vicinity of the CDA buoy, as well as over the northwest and southeast flanks of the mound. Volume calculations have determined an additional of 51,000 m³ (43%) of CDM detectable through the use of successive bathymetric surveys had accumulated over the CLIS bottom (Appendix A: Table 3-2). Larger disposal barges (4000 yd³) were employed during the last phase of capping and were fundamental in the placement of a large volume of capping material in a short period of time (35 days).

Further analysis of the postcap survey shows an apparent ring of CDM approximately 375 m in diameter clearly visible as "Total Net CDM Accumulation" as well as a central "Total Net Consolidation" feature (Figure 3-22). The majority of smaller barge (700 yd³) release points appear to be north-northwest of the CDA #2 buoy position, adding to the small mound of capping material visible at the interim cap stage of development. The northern CDM feature is 3.0 m high at the apex and 110 m wide and is responsible for the irregular shape of the CLIS 94 mound. The remainder of the CDM layer exhibits several other high spots south and southeast along the ring. The 4000 yd³ capacity barges concentrated their efforts over the central area of the mound. As a result, the pocket of consolidation discovered in the analysis of earlier surveys seems to have been filled to a certain degree, as a total negative volume of 10,800 m³ is the end result (Appendix A: Table 3-2).

By tracking the three stages of development for the CLIS 94 mound, the UDM deposit appears to be successfully capped and laterally stable (Figure 3-23). The survey artifact that is visible as an irregular projection of UDM in most of the depth difference plots corresponds to the northeast apron of the CLIS 90 mound. Differences in lane

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995











Final Apparent CDM Thickness Depth Difference SAIC September 1995 versus OSI December 1994







orientation and gridding routines between SAIC and OSI are responsible for its appearance.

Due to the effects of consolidation, tracking volumes of material throughout the different phases of mound development accounted for more of the reported volumes than comparisons over long expanses of time. The cumulative volume detected by the use of multiple surveys is 204,362 m³ or 70% of the total reported volume (Appendix A: Table 3-2). Without the use of interim survey data, volume calculations detected 70,643 m³ of CDM, 44% of the reported cap material volume, and 169,624 m³ or 58% of the total material volume.

These latter calculations are typically utilized as part of most disposal and/or capping projects where depositional volumes are quantified using differences in depth between a predisposal and a postcap survey only. Results of in-depth research studies of the operations surrounding clamshell dredging and subaqueous disposal of dredged material have demonstrated an apparent 41% reduction in volume between consecutive bathymetric surveys (Tavolaro 1984). Differences of this magnitude are expected and are attributed to barge volume over-estimation, the volume of material undetectable through acoustic bathymetric data processing techniques, and dredged material consolidation over time; they do not represent actual material loss.

3.2.2 REMOTS[®] Sediment-Profile Photography

REMOTS[®] sediment-profile photography was used to document benthic recolonization, as well as map thin layers of material and assess the overall impact of dredged material deposition at the CLIS 94 disposal mound. Complete REMOTS[®] results for the disposal mound are available in Appendix B: Table 2.

3.2.2.1 Sediment Grain Size and Stratigraphy

Fresh dredged material was detected and measured at every station except for one replicate at 200N. Replicate-averaged mean dredged material thickness ranged from 8.8 cm to full camera penetration (20 cm) (Appendix A: Table 3-3). Redox rebound intervals, areas showing evidence of intermittent or seasonal oxidation below the oxidized surface layer, were noted at stations 200 m and 300 m from the center.

Physical REMOTS[®] parameters showed that the major modal grain size was consistently reported as >4 phi (silt and clay), indicating the deposition of predominantly fine-grained dredged material. However, the sediments detected at Station 100E were slightly coarser (4 to 3 phi) silts and fine sands. The replicate-averaged mean camera

penetration ranged from 12.86 cm to full penetration (20 cm), generally increasing towards the center of the mound, except at the center station (14.47 cm; Appendix A: Table 3-3). In general, the lower camera penetration values correlated with the highest surface disturbance values; values >1 cm occurred at 200S, 300E, 300N, 300W, and CTR. The primary cause of surface disturbance over the CLIS 1994 mound was biogenic activity.

3.2.2.2 Benthic Community Assessment

The replicate-averaged mean Redox Potential Discontinuity (RPD) values ranged from 0.46 cm at CTR to 4.03 cm at 300S (Figure 3-24). A gradient of RPDs increased from the center out towards the edges of the mound, ranging from approximately 0.5 cm at CTR, to 1.5 cm at 100 m, to 2-4 cm at 300 m. The overall average RPD value for the mound was 1.76 cm, despite indications of low dissolved oxygen resulting from hypoxic conditions within the bottom waters over many REMOTS[®] sediment-profile photography stations (100W, 200S, 200W, 300E, 300N, 300S, 300W).

No methane was noted in any photograph obtained on the surface of the CLIS 94 mound. However, the RPD depths varied among replicates of the same station, indicating a patchy benthic environment. Replicate A at Station 300S exhibits a mean RPD depth of 5.87 cm indicative of a healthy benthic environment (Figure 3-25A). Conversely, replicate B of Station 300S displays a shallow RPD and indications of low dissolved oxygen (Figure 3-25B).

The successional stage status was relatively advanced for Station 300S and the remainder of the CLIS 94 mound as an area recently impacted by dredged material (Germano et al. 1994). Station 100W was the only station without evidence of Stage III organisms in any of the replicates (Figure 3-26). The most common stages noted in the replicate photographs were Stage I and Stage I on III. Median Organism-Sediment Index (OSI) values of the replicates ranged from -1 at 200S (low RPD, low DO) to 9 at 200N. Low OSIs (<6) are concentrated along the western and southern arms of the grid primarily due to the indication of a low dissolved oxygen event (Figure 3-24).

3.3 FVP Mound

The experimental FVP mound, located in the far northeast quadrant of CLIS, was monitored extensively as part of the Field Verification Program during the 1980s. Historically, benthic infaunal communities inhabiting the FVP sediments have been more susceptible to benthic disturbances, relative to other CLIS mounds. Composed of uncapped UDM deposited in 1983, the FVP mound continues to be periodically monitored as part of the DAMOS Program. No bathymetric data were collected over the historic

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Figure 3-24. Distribution of RPD (cm) and OSI values over the CLIS 94 mound, overlaid on September 1995 bathymetry and final detectable margin of the mound





Figure 3-26. Distribution of successional stage assemblages over the CLIS 94 mound, overlaid on September 1995 bathymetry and final detectable margin of the mound

FVP mound during the September 1995 survey at CLIS. However, a full thirteen-station REMOTS[®] sampling grid was occupied over the mound. Complete REMOTS[®] results for the FVP disposal mound are available in Appendix B: Table 3.

3.3.1 Sediment Grain Size and Stratigraphy

Grain size and surface roughness data indicated no distinct pattern at the FVP disposal mound. The major modal grain size at every station was >4 phi, except for one replicate at 200W where the major mode was 4 to 3 phi. The replicate-averaged mean camera penetration ranged from 12.73 to 15.69 cm (Appendix A: Table 3-4). Boundary roughness values ranged from 0.52 cm to 1.33 cm. The primary cause of surface disturbance was biogenic except at individual replicates at CTR and 200E where boundary roughness was classified as physical in nature.

Dredged material was present in all stations, except for the replicates at stations 300 m from the center. At stations where dredged material was present, replicate-averaged thicknesses ranged from approximately 5 cm at 100W and 200N to full penetration (20 cm) at several stations (Appendix A: Table 3-4). The apparent absence of dredged material 300 m from the center may be attributed to complete reworking of historical dredged material, to the extent that there are no recognizable indicators commonly attributed to dredged material. Redox rebound intervals were noted in one replicate at several stations (100N, 100E, 200W).

3.3.2 Benthic Community Assessment

Replicate-averaged RPDs ranged from 0.77 cm at 100N to 2.84 cm at 200E (Figure 3-27; Appendix A: Table 3-4). This range is slightly higher than the average RPD depths measured in the three reference areas. Methane was detected in two replicates at Station 100E, but indications of low dissolved oxygen within the bottom waters were not noted in any photograph.

The majority of the REMOTS[®] stations occupied over the FVP mound displayed Stage III activity within the surface sediments. Only one station showed no evidence of Stage III organisms (100N; Figure 3-28). Replicate median OSIs ranged from 2 at 100E and 100N (low RPD, no Stage III, methane) to 8 at 300W (Figures 3-29A and 3-29B). Several stations at FVP indicated, as at the CLIS reference areas, a decrease in benthic habitat quality relative to prior monitoring surveys.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995







Figure 3-28. Distribution of successional stage assemblages over the FVP mound



3.4 CLIS Reference Areas

As part of the DAMOS tiered monitoring protocols, reference area data are collected to provide a baseline against which results from the dredged material mounds are compared. CLIS-REF has been a reference area for CLIS since the beginning of the DAMOS Program. The two newer reference areas, 2500W and 4500E, have been monitored since approximately 1987. A total of thirteen stations were occupied over the three reference areas. Complete REMOTS[®] results for the CLIS reference areas (CLIS-REF, 2500W, 4500E) are available in Appendix B: Table 4.

3.4.1 Sediment Grain Size and Stratigraphy

Physical indicators of the benthic environment include the grain size and boundary roughness of the sediment surface. The major modal grain size was >4 phi in all reference station replicates. Replicate-averaged camera penetration ranged from 8.93 cm to 13.68 cm (Appendix A: Table 3-5). Boundary roughness values ranged from 0.42 cm to 1.23 cm and were determined to be caused by biogenic or unidentifiable processes. Biological disturbance tends to be associated with a mature sediment deposit, whereas physical disturbance is often associated with recent benthic impact.

Dredged material was not identified in any photograph, and no redox rebound intervals were identified. No station exhibited indications of methane or low dissolved oxygen.

3.4.2 Benthic Community Assessment

Replicate-averaged RPD depths at all three reference areas ranged from 0.62 cm to 1.60 cm (Appendix A: Table 3-5). This is a relatively low range of RPDs for CLIS reference stations and was lower than the averaged values for all three dredged material mounds sampled in 1995. In the past, reference area RPDs ranged from 0.55 cm to 2.7 cm during the July 1994 survey; 5.68 cm to 1.49 cm in June 1991; and 3.4 cm to 6.6 cm in July 1990 (Morris and Tufts 1997; Wiley and Charles 1995; Germano et al. 1995).

The successional stage status at all reference stations was most commonly Stage I on Stage III, indicating a mature benthic assemblage. Only one station exhibited no Stage III community in any replicates (Station 3 at CLIS-REF). Stage II was identified in one replicate at 4500E. Median OSIs at the reference areas generally ranged from 6 to 7, except for a minimum OSI of 3 at CLIS-REF Station 3 (lack of Stage III) and a maximum of 8 at 4500E Station 3. OSIs of 6 or less were present at four of five CLIS-REF stations,

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

one of four stations at 2500W, and one of four stations at 4500E. These relatively low OSIs are due primarily to the low RPDs measured in CLIS reference areas.

The REMOTS[®] photographs collected during previous monitoring surveys (July 1990, June 1991, and July 1994) indicated healthy benthic environments, with median OSI values consistently reported as 6 or above. The slight decline in habitat quality observed at several reference area stations during the August 1995 survey suggests the presence, or recent occurrence, of environmental stress (i.e., hypoxic bottom waters).

4.0 **DISCUSSION**

During the September 1995 REMOTS[®] sediment-profile photography surveys over NHAV 93, CLIS 94, FVP, and the CLIS reference areas, a trend of lower than expected RPDs and indications of low dissolved oxygen (DO) concentrations was observed. Seasonal hypoxia, due to eutrophication in the protected waters of the central and western Long Island Sound causing the degradation of water quality, had apparently affected both the benthic and near-bottom pelagic habitats. The Long Island Sound Study (LISS), a US Environmental Protection Agency (EPA) monitoring program, officially recognizes the onset of hypoxia at a DO concentration of 3.0 mg $\cdot l^{-1}$. However, the appearance of hypoxic conditions in the bottom waters and surface sediments has been documented with DO concentrations as high as 5.0 mg \cdot l⁻¹ (LISS 1990). For the past several years DAMOS monitoring activity has not included water sampling for DO or other water quality parameters as part of its field operations because the instantaneous measure during the relatively short survey period was not sufficient to determine seasonal events. However, further investigation was required to determine whether the decline in the RPD and OSI values at CLIS and the reference stations was related to disposal activity or a regional hypoxia event.

A comprehensive DO data set for stations throughout the Long Island Sound was obtained from the Connecticut Department of Environmental Protection, Water Management Division (DEP). The data was collected as part of the DEP Long Island Sound Summer Hypoxia Monitoring Program and consisted of surface and bottom DO values for 18 primary stations that were monitored throughout the year as well as a number of secondary summer stations (June to September). Seasonal monitoring stations 23, 26, and 27 and annual monitoring stations H2 and H4 were chosen due to their location relative to CLIS (Figure 4-1).

Although the data for seasonal stations 23, 26, and 27 does not continue through the September 1995 field effort, a decrease in DO concentrations $(4.5 \text{ mg} \cdot 1^{-1})$ was observed at stations 23 and 27 in mid-August (Julian Day 226) suggesting a seasonal DO event within the central Long Island Sound region (Figure 4-1). Stations 23 and 27 are situated in close proximity to the disposal site in similar water depths and bottom current patterns. Both stations show a downward progression in DO values for the summer of 1995. Station 26, approximately 7 km north of CLIS, is located in shallower water and tends to be influenced by the drainage of the Quinnipiac River and New Haven Harbor. The data at Station 26 show a drastic reduction in bottom water DO, decreasing from 8.2 mg $\cdot 1^{-1}$ to 3.4 mg $\cdot 1^{-1}$ over the first forty days of the monitoring program. Oxygen levels then show significant rebound to 6.4 mg $\cdot 1^{-1}$ on Julian Day 226, displaying higher concentrations of DO data, relative to the deeper stations.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Figure 4-1. Position of the Connecticut Department of Environmental Protection Dissolved Oxygen Sampling Stations and bottom DO trends at summer monitoring stations 23, 26, and 27 for 1994 and 1995. DAMOS survey dates added for reference.
62

The data collected at primary monitoring stations H2 and H4 also suggest a seasonal hypoxic episode was occurring in the central Long Island Sound region during the summer months. A steady decrease in detectable oxygen was observed from Julian Day 100 (7 April 1995) through Julian Day 226 (mid-August; Figure 4-2). As the water temperature began to increase in the spring and summer months, water quality in Long Island Sound was slowly depressed by falling DO concentrations and lack of significant fresh water input from the surrounding tributaries due to drought.

Station H4 was located in the center of Long Island Sound, approximately 6 km southeast of CLIS, in water 30 m deep (Figure 4-1). Bottom DO concentrations at Station H4 dropped to 4.2 mg $\cdot I^{-1}$ in early August and remained at those levels through the September 1995 survey. Station H2 showed a major decrease in DO in early and mid-August, with values falling to 2.4 mg $\cdot I^{-1}$ then slowly increasing to 3.8 mg $\cdot I^{-1}$ by late August. This station was located 6.5 km northwest of the center of CLIS in water 15 m deep (Figure 4-1).

In September, dissolved oxygen concentrations began to climb towards 6.0 mg·1⁻¹ and continued to increase as the autumn of 1995 progressed. The primary and secondary station data both indicated a decrease in dissolved oxygen concentrations within the central Long Island Sound region immediately preceding the September 1995 field activity. The REMOTS[®] sediment-profile photographic survey over the project mounds and reference areas at CLIS observed the aftermath of the hypoxic event within the benthic community. Although DO concentrations seemed to be increasing at the time of the RÉMOTS[®] survey, complete recovery within the benthic community (OSI values \geq 6, deep RPD, presence of Stage II and Stage III assemblages) would not be seen for several weeks.

The degree and effects of the seasonal hypoxia varied with the sampling location at CLIS during the 1995 monitoring cruise. In general, the CLIS reference areas showed a decline in benthic habitat quality with lower RPD depths than expected and no Stage II organisms present. The NHAV 93 mound showed improvement relative to the July 1994 survey; Stage I organisms occupied the surface sediments, and Stage III individuals were present at depth. The CLIS 94 mound recovered better than expected with a Stage I on III recolonization status, and several deep RPD measurements, but displayed indications of a low DO event. The FVP mound continued to exhibit difficulty in fully establishing and maintaining a stable benthic community with low RPD and OSI values near the mound center.

The REMOTS[®] data from the FVP mound show a steady decline in the apparent RPD and OSI since the 1991 CLIS survey, with the exception of Station CTR, where the OSI has ranged from 4 to 6 since the 1987 CLIS survey (Figures 4-3 and 4-4). This trend was also noted in the data collected during the CLIS survey in November 1993. The

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995



Figure 4-3. Histogram displaying recorded RPD calculations from June 1991, November 1993, and September 1995 at Stations 100E, 100N, 100W, and CTR over the FVP mound

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

64





Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

66

benthic population at FVP appears to be more susceptible to environmental stress than the benthic infaunal populations of the capped mounds. As a result, hypoxic events or other disturbances tend to have a more pronounced and longer lasting effect on the invertebrates inhabiting the uncapped sediments of FVP.

The Field Verification Program was concluded in 1988 with a report which determined that, in comparison to upland containment and wetland creation, subaqueous mound development within a designated disposal site is the most environmentally sound method of disposing of large volumes of UDM (Peddicord 1988). The FVP mound was targeted for capping during the 1993 disposal season using excess CDM generated by the New Haven Harbor maintenance dredging project. A lack of an adequate volume of CDM during the NHAV 93 mound development caused the deletion of the FVP capping operations phase of the project (Morris et al. 1996).

However, in order to improve the conditions of the benthic environment over the FVP mound, an effort should be made in future disposal seasons to cap the experimental mound with a 0.5 m thick layer of CDM. In addition, the adoption of the FPEIS disposal site center of CLIS shifts the entire disposal site 362 m west-southwest, leaving the majority of the FVP mound outside of the disposal site boundaries. In order to officially conclude the EPA/WES joint experiment, the area surrounding the FVP mound, ideally, should be restored to near ambient conditions with the placement of a silt cap over the exposed UDM deposit.

The cap over the NHAV 93 mound continues to support a stable benthic community with marked improvement at stations CTR, 200N, and 400S relative to the July 1994 survey (Morris and Tufts 1997). Despite a decrease in dissolved oxygen, the mound was supporting Stage I and Stage III individuals in the surface and subsurface sediments. There was a noticeable lack of Stage II individuals over all three project mounds as well as the three reference areas, suggesting an intolerance to lower water column induced DO concentrations. The Stage I surface dwellers may have been able to tolerate the hypoxia or may be the pioneering species recolonizing the sediments as DO concentrations began to increase.

The overall integrity of the NHAV 93 mound remains uncompromised eighteen months after the completion of the New Haven Capping Project. There were no noticeable changes in size or shape over the NHAV 93 mound, indicating the large bottom feature is stable. The moderate consolidation detected since the completion of capping operations is well within the forecast norm. The mound is expected to continue to consolidate as pore water extrusion and basement material compression yield to the shear weight of the capped sediment deposit over the coming years (Poindexter-Rollings 1990).

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

Geotechnical cores collected over the NHAV 93 mound within the past two years have attempted to document the development and subsequent consolidation of the NHAV 93 mound. Despite the use of precision navigation and consistently revisiting stations, the observed heterogeneity within the UDM and historic dredged material layers of the NHAV 93 mound tends to lessen the ability to track sediment layers through the five-member time-series data set. A certain degree of repeatability within the collected sediments was required to follow individual sediment strata throughout the project, providing a baseline used to quantify changes in layer thickness. However, cross-sections of a dredged material mound have been proven to be valuable as "snapshot" data as well as ground-truth data for comparison with subbottom profiling (Morris and Tufts 1997).

Geotechnical coring as an investigative technique could be improved by acquiring longer cores to obtain a sample of the ambient bottom throughout the time-series data set. The gravity coring device utilized during the New Haven Capping Project had difficulty penetrating the consolidated center of the 2.5 m high NHAV 93 mound, resulting in partial recovery. The use of a pneumatic vibrocore equipped with a 5 m steel core barrel would ensure complete penetration into the basement material to provide a baseline for consolidation measurements. In addition, the use of chemical sampling of the recovered sediment could provide valuable information on the origins of the various strata. Determination of the relative concentrations of various contaminants would allow for the differentiation of basement, historic, UDM, and CDM layers in either ubiquitous or heterogeneous samples.

The use of repetitive bathymetric surveys during the New Haven Capping Project was proven to be an invaluable tool in observing the usually hidden dynamics of dredged material mound construction (Morris et al. 1996). The same technique was employed during the post processing of the CLIS 94 mound bathymetric survey data. A total of four bathymetric survey data sets were used to follow the construction of the CLIS 94 mound and expose the accumulation and consolidation of the bottom feature. By utilizing SAIC's July 1994 and September 1995 surveys in conjunction with OSI's December 1994 and April 1995 data sets, the events leading up to the final capped mound could be tracked and volumes of material calculated.

In the past, efforts have been made to account for differences in the volume of material reported in disposal barge logs to the volumes of material detected acoustically. The issue of mass balance has become clouded by large volumes of undetectable mound apron material, over-estimation of barge volume by on-site inspectors, and compaction of dredged material on the seafloor (Tavolaro 1984). The repetitive surveys over the CLIS 94 mound have found central mound consolidation during disposal and capping activity to

68

be another factor causing large discrepancies between barge estimates and detected volumes. By restricting the window of analysis to the area immediately around the CLIS 94 mound and performing various depth and volume differencing routines, physical changes in the dredged material deposit and in the volume of material were detected.

A large central pocket of dredged material consolidation within the CLIS 94 mound was detected during the interim cap survey of the bottom feature. This pocket of consolidation is believed to be the chief cause of the mass balance shortfall. Although the use of multiple surveys improved the tracking of large volumes of material disposed, rapid consolidation due to compression and de-watering complicate precise volume comparisons.

Studies conducted at CLIS by the US Army Corps of Engineers, Waterways Experiment Station (WES), have documented significant amounts of dredged material consolidation over short periods of time (0.5 m in 30 days; Poindexter-Rollings 1990). The observed behavior of the CLIS 94 mound supports those findings with up to 1.0 m of consolidation over a 126-day period of time without evidence of UDM surface movement or collapse of the mound. If the CLIS 94 mound continues as predicted, the mound should subside an additional 0.5 m to 0.75 m over the next year and then show gradual reduction due to compression of the basement material over the next 5 to 10 years.

5.0 CONCLUSIONS

The September 1995 field efforts at CLIS allowed SAIC and NED to examine three bottom features constructed by three different dredged material management approaches. The NHAV 93 mound is an example of a highly successful CAD structure. The mound was found to have maintained its lateral stability and cap integrity. The site management strategy of creating a ring of mounds from smaller disposal projects to accept large quantities of dredged material within the basin has proven to be an efficient method of UDM lateral containment and CAD mound construction. This management strategy should continue at CLIS in order to provide large cells of lateral containment and maximize the available space within the 6.86 km² area of the disposal site.

Overall, the NHAV 93 mound appears to be recovering from the disposal activity as anticipated (Germano et al. 1994). The mound supports a stable benthic infaunal population with Stage I and Stage III organisms present in the surface and subsurface sediments. Three areas of concern detected during the July 1994 monitoring cruise (CTR, 200N, and 400S) show marked improvement with deeper RPD depths and higher OSI values despite the occurrence of a hypoxic event in the central Long Island Sound region. The sediments of the NHAV 93 mound are expected to support a Stage II on Stage III population in the coming years barring benthic disturbance (hypoxia, trawling, etc.).

The development of the CLIS 94 mound represents the next step in the successful site management strategy. The construction of an independent capped mound to the northeast of the NHAV 93 mound begins to enclose another basin at CLIS. The CLIS 94 mound appears to be a discrete and stable bottom feature that has completely incorporated the historic CS 90-1 mound that was formed during the 1989/90 disposal season. Approximately 129,900 m³ of UDM from Norwalk Harbor, New Haven Harbor, and Long Wharf Pier projects was deposited over CS 90-1. A total of 161,000 m³ of CDM was placed over the unsuitable material to isolate it from the marine environment. A CDM to UDM ratio of 1.24:1.0 was found to be sufficient to cap the UDM deposit without lateral containment as both disposal and capping operations were consistently controlled.

The overall size and shape of CLIS 94, as well as the volume of new material detected by bathymetry, suggests that mound development proceeded without difficulty. Comparisons between the July 1994 (baseline) and September 1995 (postcap) surveys performed by SAIC and the results of a precap and interim cap bathymetric surveys obtained through Ocean Surveys, Inc. support that conclusion. Intensive analysis of the four data sets detected significant central consolidation within the UDM layer during the first phase of capping operations, supporting previous studies performed by WES in the 1980s. Up to 1.0 m of dredged material subsidence was detected over a 126-day period

70

between the precap and interim cap surveys of the CLIS 94 mound. The pocket of central consolidation was responsible for a large percentage of a $121,300 \text{ m}^3$ shortfall in the mass balance of material. However, agreement between the reported barge volume and the volume detected acoustically improved by tracking the volume through the four phases of mound development.

Physical and biological indicators of overall benthic community health suggest the CLIS 94 mound is recovering faster than expected. A few stations displayed signs of low dissolved oxygen; however, the majority of the mound was characterized with moderate to deep RPDs and evidence of Stage III organism activity. As a result, the overall OSI value of 5.23 suggests the CLIS 94 mound should reach full recovery (RPD > 6) in the next two years.

Conversely, the FVP mound, composed of an uncapped UDM deposit, is continuing to show signs of low habitat quality with shallow RPDs and low OSI values over the center of the mound. Although the regional hypoxic event may have contributed to the problems at FVP, the mound has traditionally been more susceptible to benthic disturbances and slower to recover, relative to other project mounds. Now that the Field Verification Program is complete and long-term monitoring has documented a chronic response, the FVP mound should be capped in order to isolate the UDM from the sediment/water interface and return the area to near-ambient conditions. In addition, the movement of the disposal site boundaries to the west-southwest lends further support to this recommendation.

The low water column dissolved oxygen event that seemed to affect the FVP mound was also noticed over the CLIS 94 and NHAV 93 mounds, as well as the three CLIS reference areas (CLISREF, 4500E, and 2500W). Data obtained from the Connecticut DEP indicated a summer hypoxia event occurred several days before the September 1995 monitoring cruise. The REMOTS[®] photographs obtained over the reference areas and project mounds depict the aftermath of the low DO event within the benthic community. The Stage I organisms occupying the surface sediments could represent benthic recolonization as the DO concentrations began to rise approximately 10 days before the survey. In order to avoid a downward trend or skew in future data, monitoring cruises in the western and central Long Island Sound should be scheduled for early July. By conducting environmental sampling activity earlier in the summer and avoiding the possibility of recurring hypoxia, NED will gain a more realistic perspective of the benthic community at the Long Island Sound disposal sites.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

6.0 **REFERENCES**

- Fredette, T. J. 1994. Disposal site capping management: New Haven Harbor. Reprinted from Dredging '94, Proceedings of the Second International Conference, November 13-16, 1994. US Army Corps of Engineers, New England Division, Waltham, MA.
- Germano, J. D.; Parker, J.; Wiley, M. B. 1995. Monitoring cruise at the Central Long Island Sound Disposal Site, July 1990. DAMOS Contribution No. 94 (SAIC Report No. SAIC 90/7594&C89). US Army Corps of Engineers, New England Division, Waltham, MA.
- Germano, J. D.; Rhoads, D. C.; Lunz, J. D. 1994. An integrated, tiered approach to monitoring and management of dredged material disposal sites in the New England Region. DAMOS Contribution No. 87 (SAIC Report No. SAIC-90/7575&234). US Army Corps of Engineers, New England Division, Waltham, MA.
- Long Island Sound Study (LISS). 1990. Status report and interim actions for hypoxia management. US Environmental Protection Agency, Region I, Boston, MA and Region II, New York, NY.
- Morris, J. T.; Tufts, G. J. 1997. Monitoring cruise at the Central Long Island Sound Disposal Site, July 1994. SAIC Report No. 327. Final report submitted to US Army Corps of Engineers, New England Division, Waltham, MA.
- Morris, J. T.; Charles, J.; Inglin, D. C. 1996. Monitoring surveys of the New Haven Capping Project, 1993-1994. SAIC Report No. 319. Final report submitted to US Army Corps of Engineers, New England Division, Waltham, MA.
- Morton, R. W. 1983. Status report: disposal operations at the Central Long Island Sound Disposal Site. SAIC Report No. C25. Submitted to US Army Corps of Engineers, New England Division, Waltham, MA.
- Mueller, C. 1994. Results of the Central Long Island Sound Disposal Site sediment testing: October 1994. SAIC Environmental Testing Center report submitted to SAIC Marine Environment Division, Newport, RI.
- Murray, P. M.; Selvitelli, P. 1996. DAMOS navigation and bathymetry standard operating procedures. SAIC Report No. 290. DAMOS Reference Report. US Army Corps of Engineers, New England Division, Waltham, MA.

- Naval Underwater Systems Center (NUSC). 1979. Disposal Area Monitoring System (DAMOS) annual data report - 1978. Submitted to US Army Corps of Engineers, New England Division, Waltham, MA.
- Peddicord, R. K. 1988. Summary of the US Army Corps of Engineers/US Environmental Protection Agency field verification program. Tech. Report D-88-6. US Army Corps of Engineers, Waterways Experiment Station, Vicksburg, MS.
- Poindexter-Rollings, M. E. 1990. Methodology for analysis of subaqueous sediment mounds. Tech. Report D-90-2. US Army Corps of Engineers, Waterways Experiment Station, Vicksburg, MS.
- Rhoads, D. C.; Germano, J. D. 1982. Characterization of organism-sediment relations using sediment-profile imaging: An effective method of Remote Ecological Monitoring of the Seafloor (REMOTS[®] System). Mar. Ecol. Prog. Ser. 8:115-128.
- Rhoads, D. C.; Germano, J. D. 1986. Interpreting long-term changes in benthic community structure: A new protocol. Hydrobiologia 142:291-308.
- SAI. 1979. Stamford-New Haven disposal operation: monitoring survey report. DAMOS Contribution No. 1. US Army Corps of Engineers, New England Division, Waltham, MA.
- SAIC. 1985. Standard operating procedure manual for DAMOS monitoring activities: volume I and volume II. DAMOS Contribution No. 48 (SAIC Report No. SAIC-85/7516&C48). US Army Corps of Engineers, New England Division, Waltham, MA.
- SAIC. 1995. Sediment capping of subaqueous dredged material disposal mounds: an overview of the New England experience, 1979-1993. DAMOS Contribution No. 95 (SAIC Report No. 90/7573&C84). US Army Corps of Engineers, New England Division, Waltham, MA.
- Silva, A. J.; Brandes, H. G.; Brogan, D. R. 1996. Geotechnical characterization of the NHAV 93 mound: Coring and core processing summary, August 1995 survey.
 DAMOS Project Central Long Island Sound, New Haven Harbor Maintenance 1993-1995. Report submitted to SAIC, Newport, RI. Available from: Geotechnical Consulting Engineers, Saunderstown, RI.

Monitoring Cruise at the Central Long Island Sound Disposal Site, September 1995

- Tavolaro, J. F. 1984. Sediment budget for clamshell dredging and ocean disposal activities in the New York Bight. Environ. Geol. Water Sci. 6(3):133-140.
- US Army Corps of Engineers, New England Division. 1982. Final programmatic environmental impact statement for the disposal of dredged material in the Long Island Sound region. Waltham, MA.
- Wiley, M. B.; Charles, J. 1995. Monitoring cruise at the Central Long Island Sound Disposal Site, June 1991. DAMOS Contribution No. 97 (SAIC Report No. SAIC 92/7621&C100). US Army Corps of Engineers, New England Division, Waltham, MA.

aerobic, 25 azoic, 25 barge, ix, 4, 7, 34, 37, 44, 49, 67, 70 disposal, ix, 7, 44, 67 benthos, viii, ix, 4, 7, 8, 14, 23, 25, 49, 50, 54, 58, 59, 60, 62, 66, 69, 70, 72 ampeliscids, 25 amphipod, 25 bivalve, 25 deposit feeder, 25 macro-, 25 polychaete, 25 bioassay, 25 bioturbation feeding void, 25 Black Rock Harbor, ix, 7 body burden bioassay, 25 boundary roughness, 23, 54, 58 buoy, ix, 4, 7, 10, 14, 34, 37, 44 disposal, ix, 34 capping, viii, 1, 4, 7, 18, 34, 37, 44, 49, 66, 67, 69, 71, 72 Central Long Island Sound (CLIS) FVP, viii, ix, 7, 8, 14, 50, 54, 60, 62, 64, 65, 66, 70 Norwalk (NOR), 1, 27, 69 conductivity, 12 consolidation, viii, 9, 18, 34, 37, 44, 49, 66, 67, 68, 69 containment, viii, ix, 4, 7, 66, 69 contaminant, 67 CTD meter, 12 density, 12, 16 deposition, ix, 4, 7, 23, 25, 37, 49 detritus, viii dispersive site Cornfield Shoals (CSDS), 1 disposal site Central Long Island Sound (CLIS), viii, ix, 1, 4, 7, 8, 10, 12, 14, 16, 18, 23, 25, 27, 32, 34, 37, 44, 49, 50, 54, 58, 60, 62, 66, 67, 68, 69, 70, 71, 72,73 Cornfield Shoals (CSDS), 1 New London (NLDS), 1

dissolved oxygen (DO), 23, 50, 54, 58, 60, 62, 66, 70 dredging clamshell, 49, 73 feeding void, 25 Field Verification Program (FVP), viii, 7, 50, 66, 70 grain size, 16, 18, 49, 54, 58 habitat, 59, 60, 62, 70 hypoxia, ix, 27, 60, 62, 66, 69, 70, 71 methane, 25, 50, 54, 58 National Oceanic and Atmospheric Administration (NOAA), 12 organics, 27 oxidation, 18, 23, 49 recolonization, viii, 4, 8, 14, 18, 23, 25, 49, 62, 70 reference area, ix, 8, 14, 23, 27, 54, 58, 59, 60, 62, 66.70 reference station, 8, 58, 60 REMOTS®, viii, ix, 7, 14, 18, 25, 27, 49, 50, 54, 58, 59, 60, 62, 70, 72 boundary roughness, 23, 54, 58 Organism-Sediment Index (OSI), ix, 23, 25, 27, 34, 37, 49, 50, 59, 60, 62, 65, 67, 69, 70 redox potential discontinuity (RPD), ix RPD REMOTS®, redox potential discontinuity (RPD), ix, 23, 25, 27, 50, 54, 58, 59, 60, 62, 64, 69, 70 sediment clay, 27, 32, 34, 49 gravel, viii, 27, 32, 34 sand, 27, 32, 34 silt, 27, 32, 34, 49, 66 sediment sampling cores, 9, 14, 16, 27, 32, 67, 72 shore station, 10 statistical testing, 7 stratigraphy, 18, 49, 54, 58 succession pioneer stage, 25, 66 successional stage, 25, 50, 58 survey baseline, 12, 18, 27, 34, 37, 44, 58, 67, 69

bathymetry, viii, ix, 7, 8, 10, 12, 14, 18, 34, 37, 44, 49, 67, 69 predisposal, 49 REMOTS®, 14, 25, 62 subbottom, 67 temperature, 12, 62 tide, 10, 12 topography, 8, 10 toxicity, 25 trawling, 8, 69 volume difference, 37, 44 estimate, 37

waves, 12

APPENDIX A TABLES

•

APPENDIX A TABLES

•

Table 2-1.	September 1995 Central Long Island Sound Disposal Site REMOTS® Camera Stations
Table 2-2.	August 1995 Central Long Island Sound Disposal Site Geotechnical Core Positions and Lengths
Table 3-1a.	REMOTS [®] Parameters Summary Table for the September 1995 Survey of the NHAV 93 Mound
Table 3-1b.	REMOTS [®] Parameters Summary Table for the July 1994 Survey of the NHAV 93 Mound
Table 3-2.	Summary Table of the Reported and Detected Volumes of Dredged Material Disposed over the CLIS 94 Mound
Table 3-3.	REMOTS [®] Parameters Summary Table for the September 1995 Survey of the CLIS 94 Mound
Table 3-4a.	REMOTS [®] Parameters Summary Table for the September 1995 Survey of the FVP Mound
Table 3-4b.	REMOTS [®] Parameters Summary Table for the November 1993 Survey of the FVP Mound
Table 3-4c.	REMOTS [®] Parameters Summary Table for the June 1991 Survey of the FVP Mound
Table 3-5.	REMOTS [®] Parameters Summary Table for the September 1995 Survey of the CLIS Reference Areas

.

Appendix A: Table 2-1

Area	Station	Latitude	Longitude
NHAV 93	CTR	41° 09.122' N	72° 53.453' W
41° 09.122' N	200N	41° 09.230' N	72° 53.453' W
72° 53.453' W	400N	41° 09.338' N	72° 53.453' W
	600N	41° 09.446' N	72° 53.453' W
1	2005	41° 09.014' N	72° 53.453' W
	400S	41° 08.906' N	72° 53.453' W
	600S	41° 08.798' N	72° 53.453' W
	200E	41° 09.122' N	72° 53.310' W
	400E	41° 09.122' N	72° 53.167' W
	600E	41° 09 122' N	72° 53 024' W
	2001	41º 09 122' N	72° 53 596' W
	ADDIN	41º 00 122' N	72° 53 730' W
1	6001	41º 00 122 N	72* 52 882' \
-	00044	41 U3.122 N	72 53.002 VV
CLIS 94	CTR	41° 09.343' N	72° 53.099' W
41° 09.343' N	100N	41° 09.397' N	72° 53.099' W
72° 53.099' W	200N	41° 09.451' N	72° 53.099' W
	300N	41° 09.505' N	72° 53.099' W
[100S	41° 09.289' N	72° 53.099' W
	2005	41° 09.235' N	72° 53.099' W
	300S	41° 09.181' N	72° 53.099' W
	100E	41° 09.343' N	72° 53.028' W
	200E	41° 09 343' N	72° 52 956' W
	300E	41° 09 343' N	72° 52 885' W
	1001	41º 00 242' N	72 52.000 W
	10000	448 00 0401 N	72 53.171 44
	20000	41° 09.343' N	12 33.242 VV
	30000	41° 09.343' N	72-53.313 W
	070		708 54 7501144
FVP	CIR	41- 09.390 N	72° 51.750 W
41° 09.390' N	100N	41° 09.444' N	72° 51.750 W
72° 51.750' W	200N	41° 09.498' N	72° 51.750' W
	300N	41° 09.552' N	72° 51.750' W
1	1005) 41° 09.336' N	72° 51.750' W
	2005	41° 09.282' N	72° 51,750' W
	300S	41° 09.228' N	72° 51 750' W
	100E	41° 09.390' N	72° 51,679' W
	200E	41° 09.390' N	72° 51.607' W
	300E	41° 09.390' N	72° 51,536' W
	100W	41° 09,390' N	72° 51.821' W
	200W	41° 09 390' N	72° 51 893' W
	3001/	41° 09 390' N	72° 51 964' W
	00000	41 00.000 11	12 01.004 11
2500 \/	STAT 1	41º 09 227' N	72" 55 640' 14
449 00 054141	OTAT O	449 00 4051AL	70° EE AGENAA
41° 09,254 N	STAL 2	41° 09,195' N	72 55.465 VV
72° 55.569' W	STAL 3	41° 09.267' N	72° 55.567' W
	STAT. 4	41° 09.356' N	72° 55.664' W
4500 E	STAT. 1	41° 09.302' N	72° 50,638' W
41° 09.254' N	STAT. 2	41° 09.247' N	72° 50.583' W
72° 50.565' W	STAT. 3	41° 09.133' N	72° 50.602' W
	STAT. 4	41° 09.407' N	72° 50.518' W
CLIS REF	STAT. 1	41° 08.094' N	72° 50.106' W
41° 08.085' N	STAT. 2	41° 08.076' N	72° 50.028' W
72° 50.109' W	STAT. 3	41° 07.957' N	72° 50.007' W
	STAT. 4	41° 08.104' N	72° 50.238' W
	STAT 5	41° 08,135' N	72° 50,112' W

September 1995 Central Long Island Sound Disposal Site REMOTS® Camera Stations Horizontal Datum: North American Datum of 1927

Appendix A: Table 2-2

August 1995 Central Long Island Sound Disposal Site Geotechnical Core Positions and Lengths Horizontal Datum: North American Datum of 1927

Core Name	Latitude	Longitude	Length	Replicate of:
GC-1	41° 09.280' N	72° 53.334′ W	128 cm	W S
GC-2	41° 09.180' N	72° 53.385' W	125 cm	Y
GC-3B	41° 09.134' N	72° 53.458′ W	185 cm	(บ
GC-4	41° 09.078' N	72° 53.536′ W	133 cm	X
GC-5	41° 08.996' N	72° 53.629′ W	269 cm	i v
GC-6	41° 09.182' N	72° 53.509′ W	272 cm	. Z
GC-7	41° 09.100' N	72° 53.403′ W	223 cm	[•] Z1
GC-8	41° 09.136' N	72° 53.443′ W	161 cm	U
GC-9	41° 09.175' N	72° 53.407' W	131 cm	Y
GC-10	41° 09.075' N	72° 53.521′ W	248 cm	X
GC-11	41° 09.264' N	72° 53.306' W	262 cm	l w
	<u>.</u>			L

Appendix A: Table 3-1a

REMOTS® Parameters Summary Table for the September 1995 Survey of the NHAV 93 Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness (cm)
200E	1.77	4	15.7	15.50	0.42
200N	3.08	7	18.38	18.22	0.91
200S	1.24	4	17.33	17,09	0.48
200W	1.61	7	15.39	12.66	0.58
400E	4.23	11	18.91	9.45	0.79
400N	1.95	7	15.05	0	0.58
4005	1.81	8	17.74	14.68	0.66
400W	2.31	9	12.86	9.80	1.82
600E	0.91	2.5	18.08	15.42	0.86
600N	2.49	10	13.97	0	0.81
600S	1.42	5	14.78	3.01	1.29
600W	3.84	6	14.83	0	0.94
CTR	1.22	3	16.56	16.22	0.54

Appendix A: Table 3-1b

REMOTS® Parameters Summary Table for the July 1994 Survey of the NHAV 93 Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
ļ	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness
200E	0.61	2	19.61	20.00	0.71
400E	1.50	IND	16.45	17.29	3.78
600E	0.35	5	15.48	10.07	1.20
200N	0.80	.3	19.56	19.48	0.18
400N	1.20	6	17.47	18.28	1.49
600N	0.52	6	14.70	15.21	0.86
200S	1.12	3	17.26	17.94	2.86
400S	0.47	3	14.09	9.16	1.83
600S	1.11	5	10.87	11.18	1.10
200W	1.20	4	15.90	16.77	1.86
400W	0.59	4	16.85	17.47	1.01
600W	0.88	3	16.64	17.02	0.80
CTR	0.78	2	17.97	18.61	1.18

IND = Indeterminate

•

Appendix A: Table 3-2

Surveys	Positive Volume (m³)	Negative Volume (m³)	Estimated Barge Volume (m ³)	% of Estimate Detected
Baseline vs. Precap	114,704	11,245	129,900	88
Precap vs. Interim	38,664	26,449	41,700	93
Interim vs. Postcap	50,994	10,788	<u>119,3</u> 00	43
Sum	204,362	48,482	290,900	70
Precap vs. Postcap	70,643	18,222	161,000	44
Baseline vs. Postcap	169,624	13,744	290,900	58

Summary Table of the Reported and Detected Volumes of Dredged Material Disposed over the CLIS 94 Mound

Note: 11,245 m³ negative volume due to consolidation over visible portions of the NHAV 93 mound.

Appendix A: Table 3-3

REMOTS[®] Parameters Summary Table for the September 1995 Survey of the CLIS 94 Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness (cm)
100E	1.5975	8.5	20.69	18.894	0.04
100N	1.38	7	19.06	18.83	0.93
100S	1.45	5	17.22	14.76	0.77
100W	1.42	3	20.42	20.19	0.28
200E	1.18	6	20.14	19.94	0.57
200N	2.8	9	17.11	8.8	0.23
200S	0.58	-1	18.16	18.0	1.15
200W	1.45	4	19.9	16.55	0.62
300E	2.88	7	17.75	16.81	1.64
300N	2.11	7	12.86	10.6	1.22
300S	4.03	7	19.34	11.0	0.48
300W	1.54	3.5	16.98	10.71	1.59
CTR	0.46	2	14.47	14.06	1.13

Appendix A: Table 3-4a

REMOTS® Parameters Summary Table for the September 1995 Survey of the FVP Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness (cm)
100E	1.08	2	14.56	13.98	1.17
100N	0.77	2	14.78	14.36	0.52
100W	1.72	7	15,1	4.92	0.8
200E	2.84	4	15.69	15.27	0.81
200N	1.07	7	12.73	4.91	1.03
200W	1.43	7	13.36	2.64	0.63
300E	0.96	6	15.57	0	1
300N	1.1	4	13.36	0	1.33
3005	2.13	7	15.19	0	0.74
300W	2.38	8	15.25	0	1.05
CTR	2.36	6	15.68	15.41	1.22

Appendix A: Table 3-4b

REMOTS® Parameters Summary Table for the November 1993 Survey of the FVP Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness
100E	1.80	3.67	9.58	NA	1.40
50E	2.03	4.00	10.20	NA	0.56
100N	1.72	4.00	13.26	NA	0.72
50N	1.75	4.00	10.39	NA	1.57
100S	1.81	4.00	13.60	NA	0.47
50S	1.62	3.50	9.14	NA	0.61
100W	1.71	4.00	12.43	NA	1.69
50W	1.83	5.67	15.39	NA	0.39
CTR	1.23	2.67	9.49	NA	0.59

NA = Not analyzed.

Appendix A: Table 3-4c

REMOTS® Parameters Summary Table for the June 1991 Survey of the FVP Mound

Station	Mean RPD	Median	Mean Camera	Mean Dredged Material	Boundary
	(cm)	OSI	Penetration (cm)	Thickness (cm)	Roughness
100E	1.42	8	13.80	13.56	0.40
200E	2.21	10	14.31	13.56	0.70
300E	2.52	10	15.46	15.20	1.31
50E	2.16	8	14.50	14.50	1.01
100N	1.85	8	14.10	14.08	0.82
200N	1.88	10	15.20	15.34	1.29
300N	1.90	11	13.34	10.31	1.52
1005	1.04	10	13.55	13.24	0.54
200\$	3.27	10	16.76	17.06	0.88
300\$	2.32	9	13.44	11.09	1.90
100W	2.71	7	16.32	16.22	1.18
200W	1.50	9	11.46	11.38	1.22
300W	1.85	8	12.16	12.21	2.20
50W	2.47	4	16.31	16.33	1.21
CTR	1.89	6	15.97	16.25	0.79

Appendix A: Table 3-5

	· •				
Reference	Station	Mean RPD	Median	Mean Camera	Boundary
Area		(cm)	OSI	Penetration (cm)	Roughness (cm)
CLIS-REF	STA1	0.76	6.5	8.93	1.16
CLIS-REF	STA2	0.62	6	8.16	0.58
CLIS-REF	STA3	0.98	3	9.73	0.42
CLIS-REF	STA4	0.83	6.5	11.74	0.47
CLIS-REF	STA5	0.93	7	11.4	0.73
2500W	STA1	1.6	7	12.92	0.71
2500W	STA2	1.37	7	13.51	0.82
2500W	STA3	1.28	7	13.68	0.99
2500W	STA4	0.82	6	13.49	0.87
4500E	STA1	1.23	7	11.67	1.23
4500E	STA2	1.13	7	13.47	0.57
4500E	STA3	1.25	8	12.66	0.52
4500E	STA4	0.89	6	11.24	0.89
		·]			

REMOTS[®] Parameters Summary Table for the September 1995 Survey of the CLIS Reference Areas

APPENDIX B REMOTS® SEDIMENT-PROFILE PHOTOGRAPHY DATA TABLES

APPENDIX B REMOTS® SEDIMENT-PROFILE PHOTOGRAPHY DATA TABLES

Table 1.	REMOTS® Data for the September 1995 Survey of the NHAV 93 Mound
Table 2.	REMOTS® Data for the September 1995 Survey of the CLIS 94 Mound
Table 3.	REMOTS® Data for the September 1995 Survey of the FVP Mound
Table 4.	REMOTS [®] Data for the September 1995 Survey of the CLIS Reference Areas

REMOTS® Data for the September 1995 Survey of the NHAV 93 Mound

Station	Rep	Dete	Time	Successional		Grain Size (ph)		Mud Cla	1953		Carriera Pe	metration	1	Ore	ged Materia	4 Thicknes		Redox Re	shound The	17444		operent RP	O Thickness		Methene	ÓŚI	Surface	Low	Commenta
	-			Stage	Min	Max Ma	j. Mode	Number A	we Die	Min	Max	Range	Mean	Area	Min	Max	Mean	Min	Max	Mean	Anna	Min	Max	Mean			Disturbance	00	
200E	<u> </u>	08/30/95	10:14	\$1		0 74	>4	<u> </u>	0	15 53	15.12	0.58	15.63	217.49	15 34	15.92	15.55	0.75	7.00	3.91	24.91	0.78	32	1.77	NO	4	BIOGENIC	WO	OM is > or = to penetration
200€	С	06/30/05	10:16	st_i	-	ৰ সৰ	>4	4	03	15.1	15.53	0.44	15.32	209.22	15.15	15.53	15.18	0	0	0	12.615	0.05	2.96	0.69	NO	3	NO	NO	DM is > or = to penetration
200E	D	05/30/95	05:05	\$T_)		1 >4	>4	0	0	15 83	16.07	0.24	15.95	218.08	15.78	16.07	15.8	0.05	8.60	4.37	34,401	0.24	417	2.65	NO	5	SIGGENIC	NO	DM > or = to pen.
200N		06/27/95	Q4:19	\$T_1		0 >4	~4	0	0	16.94	17.72	0.78	17.33	237.17	16.75	17.62	17.15	0	0	0	15.616	0.19	1.99	1.08	NO	3	BIOGENIC	NO	DM > or = to penetration
200N	8	06/27/95	04:20	ST_ION EI		2 >4	- 14	0	0	15.85	18.05	1.21	17.45	238.43	16.8	17.86	17.24	0.78	12.25	6.53	32.071	0.05	631	2.37	NO	9	BIOGENIC	NO	DM > or = to pert.
200N	D	06/30/95	09:42	ST		0 >4	- 14	0	0	20	20.73	0.73	20.37)	281.79	59.9	20,83	20.26	1,99	12 62	7.31	79.253	3.64	8.01	5.8	NO	7	BIOGENIC	NO	DM > or = to penetration
2005	٨	06/27/95	04:08	\$T I		2 >4	N	0	0	17.91	18.45	0.53	18,18	250.81	17.77	18,59	17.94	0.24	7	3.62	14,092	0.1	3.25	0,99	NÔ	3	BIOGENIC	NO	DM is > or = to penyinition
2005	8	05/27/95	04:09	ST		1 >4	>4	5	0.11	16.36	15.89	0.53	16.63	226.33	16.17	15.6	16.33	0	ò	ō	9,467	0.05	325	1.54	NÓ	4	BIOGENIC	NO	Did is > or = to penetration
2005	ċ	05/27/05	04:10	STÎON M		1 >4	>4		0	16.99	17.38	0.39	17.18	236.21	16.54	17.33	17.01	ō	ó		8,291	0.05	374	1,18	NO	7	ND	NO	Did is > or = to pert.
200W	Á.	06/30/95	10:08	STION IN		-1 >4	>4	. 0	0	13.64	14.17	0.53	13.91	167.86	13.45	14.03	13.61	0.78	7.96	4.37	39,729	0.1	5.87	3.01	NO	10	ND :	NO	DM is > or = to penetration
200W	8	06/30/95	10:09	ST I	-	-1 >4	>4	12	1	13.59	14,17	0.58	13,88	86.79	4.03	8.2	6,26	0	0	0	10.6	0.05	2.95	0.83	NO	3	PHYSICAL	NO	OM over ambient
200W	c	06/30/95	10:09	ST_LON D		2 >4	>4	3	0.24	18 08	18.69	063	18.37	250.92	17.95	18,74	18.12	0	Ó	0	14,200	0.05	413	0.95	NO	7	IND CH	NO	DM is > or = to penetration
400E	A.	05/27/55	04:45	STION 31		4 14	>4	0	0	18.54	18.93	0.39	18,74	0	0	0	0	1.17	13.4	7.29	72.563	3.5	7.18	5.41	NO	51	BIOGENIC	NO	Relic voide?
400E	8	08/27/95	04:46	57 I ON 11		4 24		0	0.94	18.64	20.34	1.7	19.49	141.45	9.51	10.40	10.23	0.53	9.95	5.24	23,154	0.87	7.04	\$.05	NO	11	BIOGENIC	NO	RPD petchy
400E	с	06/27/95	04:47	ST		1 >4	> শ	6	0,19	18.35	18.64	0.29	18.5	253.3	18.05	16.64	18.12	0.3	12.67	8,48	32,065	0.19	5.78	2.23	NO	- 4	ND	NO	DM > or = part, 7
400N	Á.	06/27/05	04:26	STĨiON ⊯I		2 >4	>4		0	15.34	15.44	0.1	15.39	0	0	0	0	2.25	99.	6.09	53.957	1.31	6.12	3.89	NO	11	BIOGENIC	NO	Anthen?
400N	B	06/27/95	04:26	ST ON M		2 >4	>4	7	0.43	14.51	15.24	0.73	14,88	0	0	0	0	0.05	6.12	3.08	7.902	0.05	4.13	0.6	NO	6	BIOGENIC	NO	RPD petchy
400N	Ċ.	08/27/95	0427	ST_ION IN		1 >4		10	0.3	14.42	15.34	0.92	14.68	0	0	0	0	0.1	11.02	5.58	9.019	0.05	4.56	1.35	NO	7	BIOGENIČ	NO	Amblerst
4005		05/27/55	04:03	STION		Q >4	>4	. 0	0	18.54	19.17	0.63	18.85	265.33	16.59	\$9.06	18.5	•	0	0	25.077	0.29	3.22	1.77	NO		BIOGENIC	NO	DM is > or = to penetration
4005	8	06/27/95	04:04	STION		4 14	>4	5	0.18	19.37	19,47	Q.1	19.42	258.88	18.63	19.03	18.85	0	Ð	0	25.893	0.19	3,74	1.64	NO	8	BIOGENIC	NO	tiny voids at 3 and 7.5 cm depth
4005	c	06/27/95	04:04	ST_ION R		-1 >4	>4	10	0.38	14.32	15.58	1.25	14.95	92.92	3.3	8.35	6.7	0	0	0	NA	NA	NA	NA	NO	IND	IND	NO	RPD thin
40011	A	06/30/95	10:03	ST LON IN		2 >4		0	0	7.14	11.26	4.13	9.2	127,3	7.18	10.92	9.14	0	0	0	RA.	KA	NA	NA	NO	1ND	PHYSICAL	NO	AL DM2
400W	в	05/30/95	10:03	STION III		0 >4	- >4	0	0	14.27	15.39	1.12	14.63	105.34	5.73	9.61	7.63	Ó	0	0	33.119	0.15	4,13	25	NO	9	IND	NO	
400W	c	06/30/95	10:04	st_i	-	া সা	×	4	055	14.03	14.42	0.39	14.22	170.97	11.8	12.82	12.33	0	0	0	24.428	0.05	3,93	1,72	80	- 4	NŬ	HO	SM
400W	D	06/30/95	05:59	ST_LON_III		1 >4	- 14	•	0	12.38	14.03	1.65	13.2	139.41	9,17	11.89	10.09	Ô	0	0	37.014	0.73	4.17	27	NO	9	BIOGENIC	NO	PRINT for report
SCOE	Α.	06/27/95	04:40	ST_I		া সা	>4	1	0.73	17.77	18.64	0.87	18,2	147.68	9,95	11.84	10.65	0.19	10.95	5.58	20.432	0,1	2,72	1,44	NO	3	NO	NO	Relict void at 10.5 cm depth
BODE	B	06/27/95	04:41	ST_I		2 >4	>4	10	0.55	17.09	18.25	1,17	17.67	245.15	17.38	17.91	17.46	0.05	14.47	7.25	NA.	NA	HA	NA	NO	RD.	1ND	NO	DM is > or = to pers.
BOOE	c	08/27/95	06:42	ST_t		-1 >4	>4	7	0.97	18.11	18.64	0.53	18.38	253.42	17.91	18.59	18,15	0.15	14.22	7.19	5.905	0,1	0.73	0.37	NO	2	ND .	NO	DM is > or = pen.
BOON .	A	06/27/95	D6:31	STLON		2 >4	>4	0	Q	14.61	15.49	0.87	15.05	Ð	ø	Ď	0	2.44	14.06	8.57	50.103	1.5	5.24	3,75	NO	50	BIOGENIC	жo	PRINT for report (ambient)
(600N	8	06/27/95	04:32	ST_I_ON_M		2 >4		7	0 43	13.45	13.66	0.44	13.67	0	0	0	0	0.05	10.1	5.08	7.435	0.05	1.26	0.49	NO	6	BIOGENIC	NO	Antient
BOON	c	06/27/95	04:32	ST_I_ON_IR		2 >4		3	0.43	1262	13.74	1.12	13.18	0	Ð	0	0	12.95	12.96	12.96	41,727	0.19	5	3.24	NO	10	BIOGENIC	NO	Amblent
8005		06/27/95	03 52	ST_I_ON_III		1 >4		Ó	0	13,25	14 19	0.94	13.72	0	0	0	0	Ó	0	0	5.571	0.05	0,79	0.35	NÔ	6	IND	NO	Ambient
800S	8	08/27/95	03:52	TNÖ –		0 14	- 14	0	0	13 81	15.65	205	14.63	123.22	6.36	9.61	9.03	Q	Ċ	0	24.007	0.1	4.17	1.81	NO	IND	ND	NO	Lg. tracture at depth
8005	Ë	06/27/95	03.58	\$T_I		4 >4	- 14	•	٥	15 37	16 24	0.85	15.8	•	0	0	0	0	•	0	26.682	0.19	4.51	2.09	NO	- 4	RID .	NO	Ambient
ecow		05/30/95	09:54	ST_L		ત અન	- 14	0	0	14 71	15 15	0.44	14 93	0	0	0	0	0	0	0	58,414	2.43	5,58	4.48	I NO	7	BIOGENIC	NO	SM
(e00W	в	05/30/95	09 55	ST_I		1 対	>4	•	079	15 73	15 02	0 23	15 87	0	0	0	0	•	0	•	37.329	0.1	6.36	2.78	NQ	5	1ND	NO	Antient or DM?
10000	c	06/30/95	09 55	ST_LON_#	-	1 24	- 14	0	0	15 24	1573	Q 40	15 46	đ	0	0	đ	¢	đ	Û	80.509	4.27	6.75	5.76	NO	11	R()	NO	Ambient or (DM7
800W	D	06/30/95	09 59	ST		1 - 14	- 14	0	0	11 75	14 27	252	13 01	0	0	0	0	0	0	0	31.942	0.05	6.12	2.34	NO	5	ND	ю	Amblent or DM?
CTR	Α.	08/27/95	0414	ST_LON_I		1 54	- 14	0	0	1578	15 18	0.30	15 95	217 45	15 58	15 97	1579	0	0	Ô	30,395	1.03	271	2.14	NO	6	IND ,	NO	OM is > or = to penetration
CTR		05/27/95	0414	ST		4 14	4	•	0	1875	17 🖷	074	17 12	230 38	15 5	17.43	16.05	Ó	0	0	15 76	0.05	2.45	1.12	NQ	3	BIOGENIC	NO	RPD petchy
CTR	с	08/27/96	04 15	\$7_1		2 -4		•	106	113	16.85		16.6	228 78	\$23	16,95	16.21	0		Ċ	525	0.05	2 66	0.38	NO	2	240	NO	RPD v. thin

NA = Not Avalable IND = Indelarmonia ι

REMOTS® Data for the September 1995 Survey of the CLIS 94 Mound

Station	Rep	Det	1 T	Successional		Gmin Size ()	ohô	M	ud Chief			Amera Pe	natration		Dre	doed Meterie	d Thickness		Rates Re	bound The	Change .	ĥ	Contrast APO	Thirtmen		Line of	064	Surface	Low	Comments
				Stepe	1.En	Max	Mail, Mox	le Numb	er Ave	Dia	Min	Mex	Range	Mean	Area	Min	Max	Meen	Min	Max	Mean	Area	Min	Max	Since 1			Distance	00	
1006	c	05/27/	96 0251	NO		2 1	• •	4	0	0	20.74	20.24	•	20.74	287.81	29.53	20.87	20.6	0	0	- 0	NA	NA	NA	NA	NÓ	НÓ	ND.	NO	Overcementated \$44
1005	Ď	06/30/5	95 09:23	ND ND	1	2 ы	4 4 10	3	٥	۰	20.74	20.74	0	20.74	237.61	18.7	17.67	14.95	•	0		18,85	0.74	2.81	1.32	NO	HÓ	ND	NO	Overgenetwied, lower \$3 green med
TODE	Ē	06/30/5	95 09-23	ND .		2 14	e 3	4	•	•	20.74	20.74	0	20,74	287.01	20.58	20.65	20.54	0		9	12.338	0.54	128	624	NO	NÖ	ND	NO	Overpendituted
1002	a	06/30/5	95 09:25	STION B		2 **	• ,	4	¢.	•	20.44	20 44	6.2	20.54	277.23	26.39	20.58	20.37		•	8	25.367	0.15	3 56	1.87	NO		BICODINC	NO	SAL and, word at 13 cm depth
1002	Ť	09/01/5	96 0327	ST III		2 🛯	6 410	3	0	۰	20.88	20.00	0	20.89	224.12	15.49	16.41	- 14	ō	ō	é	33,431	1.72	2.81	2.35	NO	- i	ND .	NO	Oversenaimined
100N		06/27/	5 02:27	ST LON M	1	0 24	e 1	4	15	0.12	17.64	19.36	1.72	18.5	25322	17.87	19.51	18.6	•			27 902	0.49	5.62	2.58	NO		BIOGENIC	NO	(Ind > or = part; y.i.e. on stud; itschare at depth?
100N		06/27/5	95 02:21	ST I ON I		. N	4 J	4	¢.	•	18.67	19.21	0.54	18.94	256.41	18,54	19.17	\$4.41	ė.	Ó	0	0.502	0.05	0.82	0.43	NO	÷.	BICOENIC	NÓ	RPO this and patche; DM > or = to pasc; y.f.s. over must
100N	ċ	01/27/5	95 02:25	57 01 01		1 N	. ,	4	0	۰	19.48	20	0.54	1973	272.85	0.63	19.9	19.48			٥	15,767	0.05	5.74	1.12	NO	7	BIOGENIC	NO	RPD this: DM > or + to pain.; where entired; wold at \$.5 cm (400)
1005	Ă	06/27/	35 0328	8T I		1 1	4	4	ò	۰	18,37	18.41	123	18,59	280.43	13.89	18.51	16.94	0.05	15.01	7.83	15,204	0.2	2.17	1.05	NO	ż	BICOENIC	NO	SAL Child and the send dead and, on earliest
5005	ä	06/30/	95 05:44	ST FON M		1 .	4	4	0	0	14.53	15.27	0.74	14.9	205.06	14.95	15.34	14.79	•	0	0	11.008	0.30	1.63	0.76	NO	Ť	BIOGENIC	NO	Chill + or = is eas ; months Chill
1005	Ř.	09/01/	55 0128	ST I		2 1	4	4		0.74	17.50	17.90	0.34	17,78	144.25	P.95	11.55	10.56	ó	ō	0	34.349	2.07	3.4	233	NO	÷.	BICGENIC	ND	544
1004	Ä	06/27/	A5 0254	ST I		1 1	i i	4	ē.	0	20.25	20.64	0.30	20.44	285.14	15.20	20.63	20.32	ó	ō		39,125	2.51	3.16	2,44	NO	ŝ	BROODING	NO	SAC (Dalls > or + pen; Chi > or + to pen.
2000		01/27/	65 07-54	87 1		ė r	4	4	ō	٥	20.2	20.30	0.2	20.3	279.38	19.95	20.29	20.01	ō	õ	ė	20,232	0.40	2.62	1.41	NO	- Š	BIOGENIC	NO	Child b or a to persetution depth
5000	ē.	08/77/	AS 07.58	51 1		i >	i i	ai i	ā	ō	29.38	20.64	0.25	20.52	282.61	7.27	20.78	20.24	ě	ě	ā	ė				NO	ă		YES	(Ini b or a new : RPC) where present y, this
2005		06/27/	85 02:44	ST I		i r	i i	4	ō	ė	20.30	20.00	0.3	20.54	285.15	20.19	20.83	20.34	ō	ě	ā	25.475	0.34	1141	1.2	NO		BIOGENIC	ND	the penditure: This > or > to canalitation depth; Chi is stractly layers
1000	- 2	08/10/	06 00-78	ST LON 1			á i	ы.	à.	ò	19 86	20.1	0.44	19.84	281.95	18.78	26 15	1983		ñ	ā	23.004	0.00	2.84	1.65	NO		BOOFIEC	HO I	Rid barrent polycerti alci?
2005		06/30/	05 00-20	87.1		i .		ai i	ă	ō	19.51	20.4	0.96	20	272.36	15.1	20.24	19.05	ē	õ	ā	NA	NA	MA	NA	NO	ND	PHYSICAL	NO	DM h of this part what arrest sharanse RPD
2005		06/27/	AS 82-33	ST LON A			i i	ni.	ā	ō	10.4	16.5	61	16.45	121.97	6.01	985	4.4	ō	ō	á	26.372	0.44	355	225	NO		BIOGENIC	NO	or t and the Olivers and
1000		08/07/	AS 19-14	ST LON H		ŏ r	i i	4	ā	ò	18 99	17 78		17.14	0				á	ň	á	12.005	87	7.83	34	HO	11	BICOFNEC	NIC .	and the Child class and (antimeTr. \$55754)
2000	ň	08/30/	AS 00-06	ST L OH H		1 2	i i	4	ā	ò	17.59	17.44	6.0	17.76	244 1	8.54	17.86	17.8	ě	ā	ā	30 171	0.84	374	235	NO		BICGENIC	NO	Civity or a to ease : find second start, it, finding write
2007		08/17/	46 63-14	67 I		÷.			20	0.66	13.80	16.45	2.54	15 17	205.45	13.5	15.78	14 17	ě	ñ						MO	. i	PHYSICAL	VPS	(Maximum)
		00207	AS 03.05	ST LON M		A >					18 97	18.51	114	19.74	285.78	18.03	10.56	18.23	0.25	12.54	135	1004	67	1.87	100	NO		BOOFNIC	NO 1	Shit Chile or a lo see " and an extern
2000		08/07/	00 03/36	AT 1		6 2		, i	6	ö	19.8	20.25	0.14	20.07	277.81	19.78	20.15	19.30				6.97	0.15	131	1.04	NO		NO	YES	DM is or a to new decity: RPD patche: when addent
		0000		87 L CH W					ñ	ò	18.08	19.4	874	19.43	234.65	587	17.83	14.80	0.04	10	- 50	26.48	- 640	2 61	1.02	10	- i		NO.	Rat Did Andri Man
20070	- 2	00177	105 G2.50	ST LON #							19.7	20.2	0.40	19.95	214 81	14.43	10.00	11.54	01	13.8	4.85	23 151	117	2 34	1.65	NO		80	YF2	PPC antrine Chi to shoul 14 cm
20044		08/37/	AL 11-14	ST 1					ā.	ē	20	20.44	0.64	20 32	234.64	18.46	18.03	12.1	0.05	18 11	4.04	11 727	0.05	154	0.00	80		PHOTOCAL	ND	SAL
	Ť.								ě.		18.13	18.57	0.44	18.35	225.97	1451	17 57	14.25	6 07	11.02	15	13.000	0.05	2.88		140		BECOPHEC	MO.	on f annote that I small him must ald hellow
3000	- 2 -	001217	10 02:10	NO.			2		ň	ā	15.91	19.44		17 44	207.5	1578	201	17 17				MA			ليبه	NO	- mõ	PHYSICAL	YES	This is a to non-dentity burning much is assessed about a burning and invited
1000	2	08/07/	46 00-00	ST LON W						0.58	16.75	17.29	0.54	17.00	238.81	14.38	17.57	17.02	0.1	7 79	1.00	82.163	0.1		4.76	NO	11	BICGENIC	NO	Did b or b to non-death; on, v.f. specifik, biosticat, blass court
3000		00/2//	10 02:02								13.74	14 88		14 21	114.04		12 12	\$71	2 34	11114	115		5 87	517	37			BIOGENEC.	NO.	and a far and all standard stands fill its standard standards
3000	- 2 -	000210	ns 03.10	ST LON W					10	0.68	13.36	un.	1.00	13.00	100.02	113	14.33	13.55				-					ND.	NO	VEX	RPC) entries must be Chi
3001		00/21/	10 00:10								10.25	11 87		\$1.95	115 78		11 72	175				18.288	0.05		1.11	100			NO.	PBD entries
3004	ž	00/21/		AT LON H							11.07	111	140	12 30	100.07	6.05	51.64			ž		14.342	0.38		132		÷	ROOTING	NO N	Shit and b Chill
3007		06/30	10 00.10	67)			2		ň	ē	18.45	19.03	0.56	18 74	158.00		11.49	11.11	4.74	14 77	30 51	78 143	110	244	sie	NO.	÷	BICOPPIC	10	Shit must be a Cliff a crimin nam
3005		00211	10 12.14						ž	Ň	20.2	20.30		20.3	102.11	6 17	10.00	7.07	0.05	115	4.77	13 412	0.05		1 23			BOORDAC	VER	Rat BOO water militie inner
3005	2	00/2//	AB 4214	211 ON M		: :			ž.		18 67	19.31		18.07	164.78	10.05	10.0	11.1				40.573	10	1.4	2 90			BIOOFHIC	NO	Elit midde 10 bits start
3005		0001/	15 6332	31104		2 3			×.	Ň	44.38	49.47	3.00	16.78	64.77	10.00	10.0	7.0		7.00		11.000			- 37		- 1	BICODIE:	100	The base of determines made at death
30044		06/2//	100 00002	31 <u>9</u>		1 1					10.10	10.01			112 47		17.04				1.5									COC antide and an other descention
300W		06/27	195 0330	ai j.		-				0.40	47.64		1.20	17.01	+41	7.12	17.00	111	0.00	7.56	110	1404	0.00					Bucchart.	HA I	First party, easy with the strange sector
30044	÷	06/27/	ver oaron	81 <u>1</u>		1 1						47.00					12.32		0.00			14.000	0.00	2.14				BIO OFFICE		the second round water and the second s
300W		06/30	V95 09.17	STICN		2 2					10.7	1/ 54	0.30	10.9	110.0.1		W.4	14.34	0.70			8 1 4 4		125	1.00			BICKOEDEC	100	owe, meaning voice? In some internets? myse
CIR	<u>.</u>	0627	NG 02:21	21_1		: :							1.00		404 773	1.1.1	14.01				×	6.414	0.05					DADORY AL		a file DDD Fail - and station
CIR		06/27	AS 02:22	31_1		2 2				100	14.10	14.78	153	14 34	104.01	10	14.83	14.14	, i		Ň	0.216	200	1.42			- 1	BOOM DOC		the second of design in the second
	<u> </u>	06/27	6 022	ST ON M		<u> </u>	•		v		11.45			-4.30	1.0001	1.00			ų.		· · · · ·	- AR	0.00	4.11	0,000	- NV	•			and the of sides of substances and substanting shares
NA.+ Nol A	al de la companya de																													
787 - Inde	erminale																													

REMOTS® Data for the September 1995 Survey of the FVP Mound

Continuents		Short Galling and public on surface on surface way your	coll public at writes	col pulsts at earliese	H > pr = to pert, surface facial policie	and works and the stand of the	it > e = it per : RPD patchy: shall buy, debried, raid with	M > or e la pendiration depti	PD-v their vold in terms of the statistics and 7	Lives to part: RPD v. Shirt vices annual	M > er = to perintingies depti-	il is terris class in tee conter?; emblent? Inge volds at depth	ntine .		Is put epert, cinners clast on written	PD petchy; 0 cm in places		12×14		M > or a to pen.; yolds; large tumow in plane of image	sarty at DM; DM > ex = to pen; APO x; thirt; Muthus shall be	II > or e to permitation depth	Li > cr + to penetration depth	PD Induct meeting Cast	at the second second of the second second second	M > cr = to penditution depti	term at 10 cm dayof; but no voids men	odocomid	W above region of teeding voids/pub sparis?	ract of depth	ther arbitects at early, creack at depth	urbece prededitions	ome wortnes at 10 cm depth, CMP	think
š:	8	5	ء د	۳ د	۵ ۵	e 	٥ ٥	• •	• •			<u>ہ</u>	< 0		*	۳ ۵	~	*	~	<u>م</u>	±	。 。	。 。	« 	ء •	۰ م	s 0	۹ ۵	۵ ۵	° •	۶ ۵	** •	ه م	× د
			A DARDON	BUODENIC M	BUCCENC K	¥ Qu	PHYSICLE N	BLOOEDC M			BIOGENC W	BIODENC N	BOOLENC #	BIOGENIC IK	PHODENIC IN		BUODENIC III	ž	IN CHICK N	BUCCENC W	TORUGE R	# DANGOLDA	*	ž C	BUCCENC M	BUODENIC M	BIOGENIC N	ž		BUCCENIC M	¥ Gu	BOOGENIC N		QN
ð		=	•••	•		-	-		• •	• •		-	~	-	-	~	ę	•	•	5	N	•	N	~	*0	•	•	~	~	-	•	-	•	F
ł		£	Ŷ	Ŷ	2	2	£	9	1	29	Ŷ	Ŷ	Ŷ	Ŷ	Ŷ	¥	£	Ŷ	Ŷ	Ŷ	£	£	YE\$	Ŷ	YES	£	£	£	Ŷ	£	Ŷ	£	£	¥
-	1	8	117	ñ		1 23	2			5	5	1.16	10	2	0.00	10	1.11	8.0	0.0	8. #	0.01	20	5	75.0	0.07	100	1.47	÷,	14	1	1.24	2.16	0.00	8
	1	ţ	۳.	ž	9	2	ž		12	5	ŝ	50	4	31	141	8	25	80	2.62	8	9	8	5	5		Ş	3.74	5	5	3	5	ŝ	1	8
042 1000	Í	ŝ	1 20	5	10		80	80		3	5	80	8	80.0	80	800	3	5	5	12.4	5	0.15	80	8	5	800	80	800	20	8	0.1	1	0.15	ł
₹	Į	8	523	17.147	1017	1.34	17,010	-	ļ	3	14.018	16.111	13.005	2 2	10,456	10.730	20.02	1	ŝ	50.00	6.019	21.12	24.46	5	12,577	8.12	e R	18.44	19	22,315	17,206	2228	12.21	55.419
ł	5	•	•	•	•	•	•	1	ļ	• •	•	•	0	•	•	•	•	•	•	•	•	•	2	•	•	•	•	•	Ę	•	•	•	•	•
Now There	2	•	•	•	•	•	•		1	•	0	•	•	Þ	0	•	•	•	¢	•	•	•	11.05	•	•	•	•	•	121	•	•	•	•	0
Nactor Re	ġ	•	0	•	•	•	•	E	<u>د</u>	, -	•	•	•	•	•	•	¢	ø	°	•	•	•	121	•	•	•	°	¢	90	•	•	•	•	•
_ 1	5	0	•	•	16.29	16.04	2	14.57	2	R	11.24	•	•	•	•	•	•	•	•	15,80	\$ 1	15.55	11.12	<u>5</u> 22	ž	11.75	•	•	8	°	•	°	•	•
Thomas -	Į,	0	•	•	8.6	16.26	8		1	ļ	12.33	2	•	•	•	•	•	•	•	10.55	14.61	10.12	15.24	13.65	14 12	15.29	•	•	22	•	•	¢	0	•
	Ē	0	¢	٥	15.82	16.07	3	11.22	1	1	11.21	2	0	•	•	•	•	•	0	15.56	112	5.76	13.55	19.0	15,70	14.06	•	•	2.16	•	ø	•	•	•
Š	Ŧ	•	¢	•	212	223.24	192.8	100.55	i i i	W CHI	180.44	5.5	•	•	o	•	•	•	•	217.24	105.62	212.0	191.79	100.45	215.79	R 82	•	•	100.41	¢	¢	•	•	•
-	5	21.2	X ::-	5	10.01	16.6	14.01	14.61		2	12.11	12.55	2.5	3	11	1.5	15.07	15.15	15.69	16.5	1.54	10.02	14.0	13.56	15.00	22	15.07	58	12.78	1	12.72	15,29	15.29	15.37
LINCOL	ş	2	80	6	260	0.19	252	870	1	12.0	<u>.</u>	8	80	2	R.	8	20 20	8	1.15	28.0	3	0.87	a,	5	80	12.0	29.0	50	30	80	80	5	2	0.0
		R	15.68	5	56.69	16.7	15.28	14.85	8	2	12.00	10.61	13.64	14.76	15.53	8.11	18.17	15.78	10.20	16.90	14.15	16.45	8.9	14.13	19.82	5.63	15.48	15,36	13,25	14.76	13.01	15.02	15.02	15.40
3	5	ß	83	202	16.21	16.51	11.72	14.96	1	1	8	10 C	122	13.64	13.16	1721	55	14.53	5	18.02	14.27	15.51	13.65	82	13,44	16.01	14. 6 8		12.31	14.57	11.43	14,68	11.00	11 66
ž	5	•	•	•	•	0	0.38	•	• -	5	•	Ŗ	0.81	•	8	0.18	•	•	•	•	0	•	0.13	180	22	•	•	0.19	0	Ň	0	•	20	11:0
Ser Con		0	0	•	•	•	8	•	• •		•	•	4	•	•	•	¢	•	•	•	•	•	-	n	•7	٥	•	•	•	•	•	•	12	-
10-11-11-11-11-11-11-11-11-11-11-11-11-1		ž	X	7	7	X	X	X	7	X	7	X	X	X	X	X	X	X	7	X	7	X	X	X	X	X	X	X	4 49 3	7	t	X	X	X
(ind) the		X	X	X	7	7	X	X	7	7	X	ï	7	7	7	7	X	7	7	7	7	X	X	7	X	ï	7	X	7	X	7	X	X	X
ŝ	* F	÷	÷	•	7	÷	Ŧ	•	• •	• •	-	7	-	•	0	•	7	~	-	-	Ţ	•	•	~	N	•	0	•	•	~	•	•		•
UCDMINION		5		1 M	E NO L	, 	p)-	22	Ē	T ON IS	TION B			, Ip	'9	T LON R	T ON T	H ON H	, _	Ę.	ιþ	,	1.04.1	E OF		T LON. IN	I OK I	E NO I I	; ;_	1 ON E	;_	T ON E
		10 1	ю 93	60 45	8	8	*	9	10	, ya 1		45 5	9	5	9 2	5	ä	8	8 8	8 8	9 8	21	8	8	e 15	• •	9 5	8	5 5	5	9 1	8	5	2 2
			POOL/SG D	30/01/25 04:	201/10 02	20 100 00	30 38/10/8C	20 20/10/00		Sentras of	00105 05	00/01/05 05	20 20/10/00	08/01/05 05	Derotatio de	00-05/00 00	09/01/765 06.	00/01/95 06:	08/01/56 06.	00-01/05 00	09-01/060	00/01/05 06	00 90/10/80	00/01/05 06	08/01/20 00	00/01/20 00	00-01/02 00	00/01/05 05	00/01/02 00	00/01/95 06	00/01/02 00	00/1/25 00	00/01/05 06	00/01/02 06
ŝ		0	۔ م	Ű Ű	4	, ,	0				-	-	Ű	<	-	ų	<	-	Ű	<	-	ų	*	•	ů	<		Ģ	-		U	<		ő
3 (HECON		8	202	5005	a di	Ľ	E S	1001		Į	ACOH	ZODN	ž	NON	NOR	NOOR	300E	300	BOS	200	2002	2000	100E	100E	1005	toow	1001	100/	2001	2004	200V	NUM	NOX	MOOK

REMOTS® Data for the September 1995 Survey of the CLIS Reference Areas

Reference	Station	Rep	Outo	Time	Successional	G	iran Size (phi)		Hud C	lests.		amera Per	netration	T	Dredges	i Material T	hickness	Redox	Rebound	Nicenses		operant RPO	Thickness		detherne .	081	Surfaces	Low	Comments
Area					Stage	s.iin	Max Ma	nj Mode N	umber -	Ave. Die.	2.00	Max	Range I	Meen.	Anna I	din Ma	a Mee	n Min	Mar	Meen	Ame	Min	Max I	Meen			Debuttence	00	
CLIS-REF	STA1		06/30/95	10:59	ST I ON III	0) N	24	0	0	11.41	12.04	0.63	11.72	0	0	0	0	<u> </u>	5 6	17,523	0.18	2.72	1.21	MO	- 7	BIOGERIC	HO	by burnets, polychaetes
CLIS-REF	STA1		05/30/95	11:00	ND	1	>4	24		0 61	6.94	8.64	1.7	7.79	à	٥	ò	ō.	0 1	o 6	7 857	0.05	2.00	0.55	NO	IND .	MO	NÒ	Surface proded7: wiper artifacts7: burrow
CLIS-RFF	STA1	ė	05/30/95	11:01	8T I ON #	•) ×4	>4	4	0.44	67	7 87	1.18	7.28	ò	ė	ō	0	è i	0 0	7 811	61	1 75	0.57	HO.		NO.	нŌ	Sm. voids at 1 and 4.5 cm death; setchy RPO
CLUS-REF	STA2	Ă	05/30/95	10:53	STION R	1	>4	2	٥	0	6.65	7 38	0.73	7.01	ò	ö	ö	å	ō i		7 479	0.05	2.14	0.52	NO	i	BIOGENIC	NO	Burner artel voide
CLUS REF	3TA2	Ä	06/30/95	10.54	ST I ON IN) »4	- 24	2	e.	8 35	8 88	0.53	6.62	ő	ŏ	ò	õ	ě i		12 015	0.05	2.28	0.84	10	ž	BIOGENIC	NO	Number and valde: salety RPD
CLIS-REE	STA7	ē	06/30/95	10.54	81				ō	0	8.50	9.08	0.49	1.64	à	ō	å	ě.			7 587	0.05	1.65	0.51			BIOGENIC	10	RPD 0 in places
CHISOFEE	9741	Ť.	06/10/95	10:48	81.1	ė		54		0.1	8.04	6.42	0.34	0.25	ă	ă	à	ě.			30.016	0.10	221	1.0	ĩ				Chi in center?
CHIS.REF	STAS	÷	05/00/95	10.49	ST I	1		34	3	0.32	11 51	11.99	0.49	11.75		ě.		ň			4514		0.83	0.44		5	IND .		RPD thirt on leading white
CINE PEF	STAS	ř	06/10/95	10.44	81				ō		7.04		0.44	R 18	ň	ň	ň	ě.			1 11		121	1.00	Ĩ		NO	NO.	Wine effects
C110.055	STAA	Ň	08/10/95		STION III				12	0.82	13.01	13.4	0.10	13.7	š	- A		ž					2 6 2	1 17		;	IND	-	
CLO-REF	STA4	ě	Astronat	D.C.M	but the second s		1 3			1 15	10.81	11 11	0.03		ž	ě.	Ň					0.05	101			-		<u> </u>	PDC and the
CURRET	0744	5	0000000	~							10.00	19.24	0.10		š	ŏ	X	ž	*			0.05	1.74	0.0	~		1940	5	Real distance
CUIS-REF	01/0		003000	04.00							10.03		0.40	1.02		ž	, in the second	ž				0.1		0.51					BOD & h stream have at a data and h DED
CUS REP	5175	5	0001/05	00.00	ST LON IN		: 3			0.40	10.01	1.00	0.47	10.00		š		Š.			11.000	0.05	4.37	0.00			200		Report in parcel, burrow on ru, gent mus to carr .
CUS-REP	8143		0001/105	04.01	57_CON_M		(C			0.00	10.05	10.30	0.33	10.34		ž		2								MU.	200		Proper products, you at deput
CUS-REP	3145	н	UPUINS	09:02	SI_COUTIN		. ~	24	v	•	12.00	12.62	4.13	12.40	U	v	ų.	0			1 14,104	0.05	1.40	1.02	80	· •	and a	~	Entrant and rescald sore's statement in an
																•	-	-						-					
2500W	STAT	D	Uersonia	05:25	81_LON_III	-1		N			13.65	14.19	0.54	13.02	0			9			3 32,764	9.2	0.01	Z.4	80		BUGENEC		Avenue: mus at oppn motops; mag at record; you?
2500W	STAI	E.	08/30/95	05:26	şī_iei		24	~			12.17	12.96	0.78	12,56			0		•		16.108	0.05		1.12	NO	1	BIOGENIC	NO	La. voice below 9 cm; 1 wiper ert.; no al. 15 seen; arrowrit
2500W	STAI	F	08/30/95	05:27	ST_ON_III	9	X	- 24		3.37	11.47	12 66	0.78	12.27			2		0		16,256	0.2	3.99	1.20	NO	. <u>.</u>	210	NO	RPD thirt red, and, many at surf.; ig. volds at secor, arriver
2500W	8TA2	o	06/30/95	06:33	ST_LOH_H			24	1	3.37	13.99	14.96	0.98	14.46	•	0	0	0	•		26.672	0.64	3.5	1.00	NФ		BOGENIC	NO	Ambled
2500W	STA2	£	06/30/95	08:33	ST_LON_IN	-1		24			13.55	13,99	9.44	13.77	0	•	0	Q.	0 (12,162	0.15	3.55	0.67	NO	<u> </u>	NO	ю	RPD this and paicity; large voide at depth; pull-aparts?
2500W	STA2	F	06/30/95	06:34	\$T_N	•1	1 >4	24	Q.	°	11.77	12.61	1.03	12.29	•	Ŷ	0	0	•	• •	3 16,756	0.3	2.54	1.32	NO	7	DIO .	NO	i,arge vitid at dap@i (7); emblent
2500W	STA3	0	06/30/95	05:38	ST_LON_III) w	H	•	•	13	14.45	1.48	13.74	0	0	0	0	•	0 (26,264	0.05	3.96	2.07	NO		BIOGENIC	NO .	Antiert
2500W	STAJ	ε	06/30/95	06:39	\$T_I	-1	। >4	24	•	۰	13.05	13.69	0.64	13.37	•	0	¢	0	•	o (0.046	0.05	2.72	0.7	NO	2	0RD	NO	RPD this and patchy; and write
2500W	STAJ	F	06/30195	05:40	87_I_ON_M	-1	I >4		2	0.18	12.5	14.34	0.84	13.92	Ð	•	0	0	•	• •	0 14.996	0.05	3.6	1.07	жò	7	INID	ю	Large Recture at bottom; ambient
2500W	STA	0	06/30/95	06:45	ST_LON_IN	1	1 >4	24	٥	0	14 08	14.33	0.25	14.21	•	•	¢	0	0	o (22.17	0.2	3.15	1.55	NO	•	SICOENIC	NO	Large Backine at bottom; embient
2500W	STAC	E	06/30/95	06:45	ST_LON_III	-1	I M	24	٥	0	12.06	14.04	1.35	13.35	0	o	0	0	•	• •	5 7.304	0.05	1.87	0.46	NO		INO ON	NO	RPO this and patchy; shell lag; ambient
2500W	STAA	F	06/30/95	06:46	ST_1_ON_18	•1	1 24	24	5	0.63	12.41	13.4	0.99	12.91	•	0	¢	0	0	0 (0 5,185	0.05	1.48	0.43	HO-	2	IND .	YE8	RPD patchy; erosional (?); wiper emean
4500E	STAT	0	09/01/95	06:31	ST_LON_III		> >4		0	•	10.63	12.33	1.7	11.48	0	•	0	•	0		28.361	0.53	5.65	2.05	NO		BIOGENIC	NO	Antiert
4500E	STAI	٤	09/01/95	04:32	ST_1	2	2 24	>4	0	0	6.88	9.37	0.49	9.13	•	•	0	0	0	٥ (9.17	0.1	1.5	0.61	NO	2	BICGENIC	NO	Patchy RPD, this blue RSDI covering or, v.f. sand; biogenic
4500E	STA1	F	09/01/95	04:32	ST_LON_hr	-1	1 24	24	15	0 67	12.77	14.32	1.55	13.54	۰	0	•	0	¢	0 (5 14.49	0.15	3.68	\$.06	NO	7	BROGENIC	NO	Ambient
4500E	STA1	ġ.	09/01/95	04:33	WO T		» м	>4	10	067	11.94	13.11	1.17	12.53	0	•	0	C	0 1	0 () NA	NA	KA	KA	NO	RD	BIOGENIC	NO	Vilper White over profile
4500E	STA2	ō	09/01/95	04.26	ST_K	1	і мі	24	20	0 24	12 38	12.82	044	12.6	۰	C D	0	0	¢ 4	• •	> 17.77	0.05	2.91	125	NO	5	BICGENIC	NO	Podocerid?
4500E	STA2	E	09/01/95	04:27	ธ าพ		1 24		1	043	14 42	15 15	073	14.78	•	0	¢.	9	0	• •	38,136	0.05	3.79	1.28	NO	7	BIOGENIC	NO	3
4500E	STA2	Ē	09/01/95	04 27	STIONED	Ċ	0 24	24	5	0.58	12 77	133	0.53	13.03	0	÷.	ò	ė –	•	0 i	0 12.485	0.05	3.11	0,86	NO	7	BIOGENIC	HO	RPD this and patchy
4500	STAN	é.	09/01/95	04/21	STICHH	-1	1 24	24	5	0.36	12 43	13 11	0 68	12.77	ó	0	0	0	٥ ·	0 (0 21.865	0.05	3.25	1.6	NÓ		BIOGENIC	NO	
4500E	STAT	ž	09/01/95	04 21	STION	-	1 14	м	ŝ	08	13 54	14 10	063	13,86	ō	Ó.	ò	ō .	0	• •	9 11,150	0.05	4.37	1.78	NO	- ÷	BIOGENIC	NO	
asone	RTAS	÷.	09/01/95	04 72	31		1 24	24	10	0 61	11 21	11.40	0.24	11.34	õ		٥	٥	۰ ه	0 (5 31	0.05	0.83	0.36	NO	2	IND	NO	RPO v. thin: prosional?
65006	3144	'n	09/01/95	04.38	ST LON II		1 1	ы	- ii	0 18	11 07	11.00	0.92	11.53	ō	ō	ā	ò	à i	ō	8 906	0.05	1.65	0.00	NO	ē	BROGENIC	NO	
45006	STAA		09/01/95	04.34	AT LON #		1 24	24	10	0.24	9.74	10 83	1 07	10 29	ō	ò	ó	Ó.	ō ·	• •	0 20.482	0.05	3.4	1.42	HO	7	IND	NO	
asone	8144		09/01/95	64.3	31	-		н	ē		11 55	12 22	0.00	11.80	ō	ō	ō	ō	ò	ė i	8 8 373	005	1.94	0.57	NO	ż	IND .	NO	RPO thin

NO = Indetermineta

APPENDIX C

GEOTECHNICAL CORE DESCRIPTIONS

Table 1.Breakdown of the Five-member Geotechnical Core Data Set Collected over
the NHAV 93 Mound

<u></u>	<u> </u>				0 1 1 400E
Station	Baseline	Precap	Postcap	July 1994	September 1995
······································	9/21/93	11/10/93	3/15/94	7/18/94	8/29/95
Center	Core FF	Core L	Core N	Core U	Core GC-3B
Northeast	Core C	Core I	Core MM	Core Y	Core GC-9
Northeast Flank			Core R	Core W	Core GC-11
Southwest	Core A	Core G	Core P	Core X	Core GC-10
Southwest Flank			Core Q	Core V	Core GC-5
Northwest	Core D	Core J	Core T	Core Z	Core GC-6
Southeast	Core E	Core K	Core SS	Core Z1	Core GC-7
Off mound	Core B	Core H			

Breakdown of the Five-member Geotechnical Core Data Set Collected over the NHAV 93 Mound








Penetration Limit







2

0.5 m

APPENDIX D DAMOS DISPOSAL LOG TABLES

APPENDIX D DAMOS DISPOSAL LOG TABLES

Table 1.UDM Disposal Activity over the CLIS 94 Mound

Table 2.CDM Disposal Activity over the CLIS 94 Mound

Appendix D: Table 1

UDM Disposal Activity over the CLIS 94 Mound

permittee	project	disparea	dispdate	witd	xto	ytd	ztd	latdeg	latmin	longdeg	longmin	cyvol
			<u> </u>	ļ	L		ļ		ļ			
TALLAMDGE BROTHERS	NORWALK HARBOR	CUS	10-Dec-94	0	26547.3	44001.7	0	41	9.337	72	53,115	800
TALLAMDGE BROTHERS	NORWALK HARBOR	CUS	11-Dec-94	0	26547.4	44001.7	0	41	9.334	72	53.128	900
TALLAMOGE BROTHERS	NORWALK HARBOR	CLIS	12-Dec-94	0	26547.5	44001.7	0	41	9.332	72	53.14	900
CITY OF NEW WAYEN	NORWALK HARBOK		13-Dec-94	1 450/5 4	26548,4	44001,8	0	41	9.322	72	53.246	900
CITY OF NEW HAVEN	LONG WHARE PIER	CUS	01-Dec-94	10040.1		44001.5		41	0.03	72	53.267	6000
CITY OF NEW HAVEN	LONG WHARE PIER	lous	01-000-04	10044.0		44001.0			0.204	72	53.207	4000
CITY OF NEW HAVEN	LONG WHARE PIER	CUS	02-Dec-94	15044.2		44001.8	Ň	41	0.040	72	53.133 53.133	5000
CITY OF NEW HAVEN	LONG WHARE PIER	lcus	02-Dec-94	15044.3	Ìŏ	44001.8	ĺŏ	41	9 342	72	53 147	2200
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	02-Dec-84	15045.4	ĺŏ	44001.5	[0	41	9.277	72	53 294	8000
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	02-Dec-94	15043.7	i õ	44002	ō	41	9.382	72	53.068	4300
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	03-Dec-94	15043.8	io	44001.7	ō	41	9.346	72	53.071	5000
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	03-Dec-94	15044.3	ÌŌ	44001.6	Ō	41	9.32	72	53,139	2300
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	03-Dec-94	15044.1	ł	44001.8	ة ا	41	9.348	72	53.11B	5000
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	03-Dec-94	15044.3	Ö	44001,7	Ō	41	9.331	72	53.143	2800
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	04-Dec-94	15044	ō	44001.8	0	41	9,351	72	53,104	4300
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	04-Dec-94	15044.2	l o	44001.6	0	41	9.323	72	53,125	2500
CITY OF NEW HAVEN	LONG WHARF PIER	jcus	04-Dec-94	15044.4) o	44001.5	jo	41	9.306	72	53.15	6000
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	04-Dec-94	15044.3	0	44001.5	0	41	9.309	72	53,135	2000
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	05-Dec-94	15044.6) 0	44001.7	0	41	9.322	72	53.186	6000
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	05-Dec-94	15045.8	í o	44001.7	(0	41	9.288	72	53.36	4000
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	05-Dec-94	15043.6) 0	44000.7	0	41	9.239	72	53.002	6500
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	08-Dec-94	15044.1	0	44001.7	0	41	9.337	72	53.114	4000
CITY OF NEW HAVEN	LONG WHARF PIER	CUS	06-Dec-94	15044.2	0	44001.7	0	i 41	9.334	72	53.129	6600
CITY OF NEW HAVEN	LONG WHARF PIER	cus	06-Dec-94	15044.5	0	44001,6	0	41	9.314	72	53.168	4000
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	07-Dec-94	15044.3	į o	44001.6	0	41	8.32	72	53.139	. 6600
CITY OF NEW HAVEN	LONG WHARF PIER	CLIS	07-Dec-94	15044.2	0	44001.7	0	41	9.334	72	53.129	4000
CITY OF NEW HAVEN	LONG WHARF PIER	cus	07-Dec-94	15044.2	0	44001.7	0	41	9.334	72	53.129	6000
CITY OF NEW HAVEN	LONG WHARF PIER	cus	08-Dec-94	15044.2	0	44001.7	0	41	9,334	72	53.129	4000
CITY OF NEW HAVEN	LONG WHARF PIER		108-Dec-94	15044.2	0	44001,7	0	41	9.334	72	53.129	3800
CITY OF NEW HAVEN	LUNG WHARF PIER	CUS	08-Dec-94	15044.2	0	44001.7		41	9.334	72	53.129	4500
CITY OF NEW HAVEN	LONG WHARF PIER		09-Dec-94	15044.2		44001.7		41	9,334	72	53.129	6600
			109-Dec-94	15044.2		44001.7	ļ	41	0.334	72	53.129	4800
CITY OF NEW HAVEN	LONG MALARE RIER		10 000 04	15044.2	ļ	44001.7			0.004	12	53,129	3600
	LONG WHARE PIER	CUS	11-Dec-94	16044.4		44001.7	1 %	41	0.304	72	53.128	8600
CITY OF NEW HAVEN	LONG WHARE PIER	ICUS	11-000-04	15044.4		44001.0		A1	0 320	72	53.004	4000
CITY OF NEW HAVEN	LONG WHARE RIER	CUS	12 Dec-04	15044 3	ĺ	44001.5		41	0.300	72	53 135	4000
UNITED ILLUMINATING	NEW HAVEN HARROR	icus	12-Dec-94	15044.0		44001 7	1 0	A1	9.334	72	53,120	4800
UNITED ILLUMINATING	NEW HAVEN HARBOR	CLIS	13-Dec-94	15044 2		44001 7	1 0	41	9334	72	53 120	3500
UNITED ILLUMINATING	NEW HAVEN HARBOR	ICUS	13.Dec.94	15044.2	ň	440017	Ĭň	41	9.334	72	53,129	1000
			1.0-000-04	1.0044.2]		}	}		1
							1				UDM yd ^a	169900
1	{	ł	1	1	ł	1	ł		1	1	UDM m ³	129906
L	L	I	<u> </u>	<u> </u>	L	L	i		L	L	L	L

Appendix D: Table 2

CDM Disposal Activity over the CLIS 94 Mound

permittee	project	disparea	dispdate	wtd		xtd	ytd	ztci	latdeg	latmin	longdeg	longmin	cyvol
ASSOC AT THE CITY FORD YO		-		<u> </u>	4				<u> </u>	<u> </u>	l		
ASSOCAT THE GUILFORD TO	WEST RIVER CHANNEL	CUS	16-Jan-95		2	20047.1	44001.3	0	41	9.29	72	53.107	750
ASSOC AT THE GULFORD TO	WEST RIVER GRANNEL	CLIS	1/~100-95		2	20046.9	44001.2	.0	41	9.282	72	53.086	875
ASSOCIAT THE GULFORD TO	WEST RIVER CHANNEL	CLIS	18-J01-95	1	U	20047.1	44001.3	0	41	9.29	72	53,107	900
ASSUCAT THE GULFORD TO	WEST RIVER CHANNEL	CLIS	18-Jan-95		a	26547.1	44001.2	0	41	9.278	72	53.11	950
ASSOC AT THE GUILFORD YU	WEST RIVER CHANNEL	CUS	19-Jan-95		9	26547.1	44001.3	0	41	9.29	72	53.107	850
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	cus	20-Jan-95		0	26547,4	44001.4	0	41	9.296	72	53.139	650
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	ICUS	22-Jan-95		0	26547.2	44001.2	0	41	9.275	72	53.123	875
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	23-Jan-95	[0	26547.1	44001.4	0	41	9.303	72	53,103	825
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	Cus	24-Jan-95		0	26547.1	44001.3	0	41	9.29	72	53,107	750
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	24-jan-95		0	26547.1	44001.4	0	41	9.303	72	53,103	800
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	25-Jan-95		0	26547.8	44001.2	0	41	9.265	72	53.171	900
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	26-Jan-95	ŀ	0	26547.5	44001.3	0	41	9.281	72	53.155	875
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	26-Jen-95	(ΟÍ	26547.5	44001.2	0	41	9.268	72	53,159	800
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	28-Jan-95	ł	0	26547.6	44001.2	0	41	9.265	72	53,171	850
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	29-Jan-95	1	0	26547.5	44001.4	0	41	9.293	72	53,151	875
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	30-Jan-95		ol	26546.7	44000.8	0	41	9.236	72	53.077	900
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	lcus	30-Jan-95		0	26548.9	44000.8	lo	41	9.231	72	53,102	900
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	31-Jan-95	1	0	26548.7	44000.8	0	41	9,238	72	53.077	900
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	ICUS	02-Feb-95		0	26546.8	44000.8	Ó	41	9,234	72	53,089	950
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	03-Feb-95		0	26546.8	44000.8	0	41	9.234	72	53,089	950
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	11-Feb-95	1	o	26548.6	44001.1	Ō	41	9.277	72	53 053	950
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	13-Feb-95	1	ŏ	26548.5	44001	ō	41	9.267	77	53 045	000
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	lcus	14 Feb-95	1	ŏ	26546.4	44001.1	ō	41	9 282	72	53 029	1000
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	15-Feb-95		ōł	26548.4	44001	ō	41	9,269	72	53,033	1000
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	16-Feb-95		o	26546.4	44000.8	ō	41	9.243	72	53.041	850
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	17-Feb-95		ō	26547.5	44001.5	ō	41	9.306	72	53,148	800
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	18-Feb-95	ļ	ō	26547.4	44001.5	0	41	9.309	72	53,135	925
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CLIS	19-Feb-95	1	ō	26547.4	44001.5	Ō	41	9.309	72	53 135	925
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	19-Feb-95	I	0	26545	44001.4	ō	41	9.355	72	52 847	950
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	20-Feb-95		0	26547.4	44001.5	ō	41	9 309	72	53 135	800
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	21-Feb-95	ļ	ō	26547	44001.5	ā	41	9.318	72	53.087	1000
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	ICUS	21-Feb-95		ŏ	26547.1	44001.5	ŏ	41	9.316	72	53,099	975
ASSOC AT THE GUILFORD YC	WEST RIVER CHANNEL	CUS	22-Feb-95		ŏ	26547.1	44001.5	ō	41	9318	77	53 099	975
CENED-CD-EDA	STONY CREEK CT CHANNEL	CUS	24.Mar.95		ō	26547.4	44001.5	ň	41	9 309	72	53 135	850
CENED-CD-EDA	STONY CREEK CT CHANNEL	CUS	25.Mar.95	i i	ŏ	26548.9	44001.5	ō	41	0.325	72	53 074	800
CENED-CD-EDA	STONY CREEK CT CHANNEL	in is	27.Mar.05]	2	28548 8	44001 4	ň	41	0.315	77	53 042	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CUS	27-Mar.05		2	28547 4	44001 2	ň	41	0.070	77	\$2.11	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CUS	29_Mar.95		ă	26547.5	44001.2		41	0.269	52	53 160	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CHIS	20 Mar 05	1	ă	28548 4	44001 1	ň	21	9 282	72	63 029	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	20.Mac.05		ă	26546 A	44000 8	Ĭ	41	0.200	77	62 090	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	34_1407-05	ļ	Ň.	26547 5	44001 7	Ĭ		0 932	72	67.14	700
		02.0	07-11102-00	[1	20047.0		Ŭ			1 12		100

I

Appendix D: Table 2 (continued)

1

permittee	project	disparea	dispdate	wtd	xtd	ytd	ztd	latdeg	latmin	longdeg	lonamin	Cyvol
		1				ľ						
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	31-Mar-95	0	28547	44001.5	0	41	9.318	72	53.087	800
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	01-Apr-95	0	26546.5	44001.3	0	41	9.305	72	53.033	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	03-Apr-95	0	26547.1	44001.3	0	41	9,29	72	53,107	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	06-Apr-95	0	26547.5	44001.3	0	41	9.281	72	53,155	600
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	07-Apr-95	0	26548.5	44000.9	0	41	9.254	72	53.049	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	07-Apr-95	0	26547.2	44001.7	0	41	9.339	72	53,103	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	08-Apr-95	0	26547.2	44001.7	0	41	9.339	72	53,103	600
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	08-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.098	700
CENED-CD-EDA	STONY CREEK GT CHANNEL	CLIS	09-Apr-95	0	26547.4	44001.9	0	41	9.36	72	53.12	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	09-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	10-Apr-95	0	26547.3	44001.9	0	41	9.362	72	53,108	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	11-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	12-Apr-95	0	26547.3	44001.9	0	41	9.362	72	53.108	650
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	12-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	14-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	14-Apr-95	0	26547.3	44002	0	41	9.375	72	53.104	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	15-Apr-95	0	26547.1	44001.9	0	41	9.367	72	53.083	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	15-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	17-Apr-95	0	26547.3	44002	0	41	9.375	72	53.104	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	18-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	18-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	19-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	19-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	20-Apr-95	0	26547.3	44002	0	41	9.375	72	53,104	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	21-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	21-Apr-95	0	26547.3	44001.9	0	41	9.362	72	53.108	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	22-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	22-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	24-Apr-95	0	26547.3	44002	0	41	9.375	72	53.104	650
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	25-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	26-Apr-95	0	26547.2	44001.9	0	41	9.365	72	53.096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	27-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53,099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	28-Apr-95	í o	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	28-Apr-95	0	26547.2	44001.8	0	41	9.352	72	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	29-Apr-95	0	26547.2	44002	0	41	9.378	72	53.092	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	29-Apr-95	0	26547.2	44002	0	41	9.378	72	53.092	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	01-May-95	0	26547.2	44001.9	0	41	9.365	72	53.096	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	02-May-95	0	28547.1	44001.9	0	41	9.367	72	53.083	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	03-May-95	0	26547.2	44001.9	0	41	9 365	72	53 096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	03-May-95	0	26547.2	44001.9	0	41	9 365	72	53 096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	04-May-95	0	26547.2	44002	0	41	9 378	72	53 092	750
	l			1		I				i	1	ł

Appendix D: Table 2 (continued)

permittee	project	disparee	dispdate	wtd	xtd	ytd	ztd	latdeg	latmin	longdeg	iongmin	cyvol
CENED-CD-SDA	STONY CREEK CT CHANNEL	CLIS	Di Mari DE	<u> </u>	26547.2	44001.0			0.205		53 000	
CENED.CO.EDA	STONY CREEK CT CHANNEL	CLIC	OC May SS		20041.2	44000			0.300	12	53,035	1 (50
CENED-CD-SDA	STONY CREEK CT CHANNEL	CLIE	OF May OF		20041.2	44001 0			9.310	12	53.082	750
CENED-CO-EDA	STONY CREEK CT CHANNEL	CUE	OC May-05		2000112	44004.0		41	9.305	12	53,095	/50
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	00-May-05		20047.2	44000		41	0.303	1 72	53,090	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	00.1494-05	i š	20047.2	44001 0		41	0.305	1 42	53,092	750
CENED-CO-EDA	STONY CREEK CT CHANNEL	CUS	10.6fm.05		20041.2	44001.0		41	8.300	1 12	53,095	750
CENED CD EDA	STONY CREEK CT CHANNEL	CUS	10-May-95		20047.2	44001.0	Ň		0.000	12	53,080	700
CENED CD EDA	STONY CREEK CT CHANNEL	CLIS	12.444-05	ែត	26547 2	44001.0			0.205	72	53,090	1 200
CENED-CO-EDA	STONY CREEK CT CHANNEL	CLIS	12.May.05	l ă	28547 2	44001 0			0.000	70	53,090	100
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	13.May-05	l ă	26547 2	44001.0			0.303	70	53,030	200
ICENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	15.Mm-05	()	26547 2	44001 0		44	0.305	(<u><u></u></u>	62,000	700
CENED-CO-EDA	STONY CREEK CT CHANNEL	CLIS	18.May.05	1 .	26547.2	44001 0	Ň	44	0.200	72	63,080	750
CENED CD.EDA	STONY CREEK OT CHANNEL	CLIS	10-may-05	່	10547.2	44000			0.000	72	53,080	150
ICENED-CD-EDA	STONY OREEK OF CHANNEL		17 May 05		120047.2	44001 0			8.3/9		53,082	800
CENED CO EDA	STONY OREEK OT CHANNEL	CLIS	17-may-85		20041.2	44001.0		- 44	9.303	74	53,080	
CENED-CD-EDA	STONY CREEK OT CHANNEL		10 May 05		20041.2	44001.8		41	9.303		53,030	100
CENED CD EDA	ISTONY OPEEK OT CHANNEL	CLIC	to May OF	(🕺	20047.2	4001.0			0.332		53.089	100
CENED-CO-EOA	ISTONY CREEK OF CHANNEL	CLIS	19-May-85		20041.2	44001.0	- 0	41	9.352	1 12	53.099	700
CENED-CD-EDA	STONY CREEK CT CHANNEL		20-Milly-85		20041.2	44001.9	0	41	9.305	12	53,096	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIG	20-mey-30	[20047.2	44001.0	Š		0.305		50,090	100
CENED CD EDA	STONY CREEK CT CHANNEL		22-may-05		20041.2	44001.0	Ň	41	0.305	70	53.080	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	23.May.95		26547 2	44001 0	Ň	4	0.305	72	53,000	750
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	24_May-95	Ň	28547.2	44001.0	ň	41	0 365	72	53,000	700
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	24.86.05	i õ	26547 3	44001 0	2	44	0.000	72	63 400	200
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	26.May-05	ې ا	20547 2	44002	ň	41	0.378	72	52,000	400
CENED-CD-EDA	STONY CREEK CT CHANNEL	CLIS	27 May-95	l ă	26547 2	44001 0	ň	41	0.365	72	63 002	=
TILCON CONN	PINE ORCHARD MARINE TERMINAL BRANFORD	CUS	28.4nr.95	i õ	28547 4	43000 0	i õi	41	0.000	72	53 107	2082
TILCON CONN	PINE ORCHARD MARINE TERMINAL BRANFORD	CLIS	28.40-95	1 6	28547.3	44001 5	ň	44	0.311	72	53 422	2000
TILCON CONN	PINE ORCHARD MARINE TERMINAL BRANFORD	CLIS	20-An05	1 .	28545	44001 4	l õ	41	0.355	72	52 947	3554
TH CON CONN	PINE ORCHARD MARINE TERMINAL BRANFORD	CUS	20.40-05	{ õ	26547 2	44001 2		41	0.000	72	52 125	3200
TILCON CONN	PINE ORCHARD MARINE TERMINAL BRANFORD	CLIC	20 Any 05	Ĭ	28547 8	44001 4	ň		0.210	1 12	52 475	2000
TILCON CONN.	PINE ORCHARD MARINE TERMINAL BRANFORD	CLIS	20.40.05		20041.0	44000 8	Ň		0.202	72	63,063	3200
TILCON CONN.	PINE ORCHARD MARINE TERMINAL BRANFORD	CLIS	30-Apr-95	ة ا	26547.1	44001.5	i õ	4	9316	72	53,000	3227
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	30-Apr-95	Ö	26546.4	44001.5	ō	41	0.333	72	53 014	2600
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	30-Apr-95	ם ו	26547.1	44001.3	ō	41	9.29	72	53 107	3871
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	30-Apr-95	15044.3	0	44001.1	i ő	41	9264	72	53 119	2900
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	30-Aor-95	0	26548.4	44000.8	ō	41	9.243	72	53 041	3618
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	01-May-95	15043.7	0	44000.8	Ő	41	9.247	72	53.02	2800
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	01-May-95	0	26547.4	44001.4	o	41	9,296	72	53 139	3871
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	01-May-95	15044.1	0	44001.5	a	41	9.314	72	53,108	3500
TILCON CONN.	PINE ORCHARD MARINE TERMINAL BRANFORD	ICLIS	01-May-95	0	26546.5	44001.3	o j	41	9.305	72	53.033	2858
			[[]	[Ì			i -		

3

Appendix D: Table 2 (continued)

Dermittee	project	discama	disodate	wid	xtd	vtd	ztd	latdeo	Latmin	lonoden	Ionomin	Goval
J]			1			•				,
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	01-May-95	15044.2	Ó	44000.4	Ö	41	9,188	72	53.077	3300
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	02-May-95	15044.4	0	44001.3	0	41	9.283	72	53.142	3300
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	02-May-95	0	26547.2	44001.3	0	41	9.288	72	53.119	3748
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	02-May-95	0	26546.4	44000.9	0	41	9.256	72	53.037	2729
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	02-May-95	15044 2	0	44000.8	0	41	9.233	72	53.093	3200
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	02-May-95	0	26547.1	44001.6	0	41	9.329	72	53.095	3871
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	02-May-95	15044.2	0	44001.5	0	41	9.312	72	53.121	2800
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	03-May-95	0	26547	44001.3	0	41	9.293	72	53.094	3745
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	Cus	03-May-95	15044.4	0	44001.2	0	41	9.272	72	53,138	3300
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	03-May-95	0	26547.4	44001.5	0	[41]	9.309	72	53,135	3110
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	03-May-95	15044 8	0	44001.4	0	41	9.283	72	53,203	3400
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	03-May-95	0	26546.6	44001.2	0	41	9.29	72	53.05	2983
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	03-May-95	15044 1	0	44000.5	0	41	9.202	72	53.066	2500
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	04 May 95	j O	26547.5	44001.2	0	41	9.268	72	53.159	3491
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	04-May-85	0	26547.5	44001.4	0	41	9.293	72	53,151	3173
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	04-1407-05	0	26546.8	44000.2	0	41	9.157	72	53,112	2983
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	04-May-86	15044	0	44001.2	0	41	9.284	72	53.08	3200
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	04-4407-86	0	26547	44001.6	0	41	9.331	72	53.083	3300
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	Cus	04-May-86	15044.4	0	44001.2	0	41	9.272	72	53,138	3200
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	05-1487-85	0	26547	44001.2	0	41'	9.28	72	53.098	3871
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	05-144	15044	0	44000.7	0	41	9.228	72	53.06	3300
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	105-May -86	0	26547 1	44001.3	0	41	9.29	72	53.107	3110
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	05-44	15044 1	0	44001.6	0	41	9.326	72	53.11	3000
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CUS	06-May-85	150437	0	44001.4	0	41	9.315	72	53.044	3200
TILCON CONN.	PINE ORCHARD MARINE TERMINAL-BRANFORD	CLIS	05-449-85	0	26547.5	44001.3	0	41	9.281	72	53.155	529
			ł								CDM yd*	210616
		1	1	ł				ļ			CDM m ^a	161037
L			I		L	1	L	l			· ·	